

DS2020 nominal BI-2
xxxxm depth (CTD) (xxxxm multibeam)
()
nominal:

0m

2 **2x Viny 12B-3 floats on wire w/SBE37** 30m
(8 kg air wet, 40 kg net positive buoyancy)

1/2" Galv shackle

45m
1/4" Nilspin wire rope

- 1/2" Galv Pear —(A)
- 1/2" Galv
- 1/2" Galv pear
- 1/2" Galv
- 1/2" SS w/iso
- 1/2m SS chain
- 1/2" SS
- 5/8" SS
- 5/8" Galv 3-links
- 1/2" Galv Pear —(C)
- 1/2" Galv
- 1/2" Galv Pear
- 1/2" Galv
- 1/2" Galv Pear
- 1/2" Galv —(D)
- 1 m 1/2" chain
- 5/8" Galv
- 5/8" Galv 1/2" chain —(E)
- 1/2" Galv Pear
- 1/2" Galv
- 1/2" Galv Pear
- 1/2" Galv swivel —(F)
- 3/8" galv
- 1/2" Galv swivel —(G)
- 1/2" Galv
- 3/8" galv + 5/8" drop
- pear
- 3/8" SS
- 3/8" galv 1/2" chain —(H)
- 1/2 m 1/2" chain
- 1/2" galv
- 1/2" galv weak link —(I)
- 1/2" galv pear
- 1/2" galv
- 1/2" galv pear —(J)
- 7/16" galv
- 7/16" galv swivel
- 7/16" galv
- 5/16" galv
- 3x 1/2" galv 2x 3-link 5/8" drop 2x pear —(K)

1m 1/2" chain

sn
Enable
Release
Rx Tx

5/16" shackle

bridle

1 wheel

Bottom Depth 80m