

Appendix C

Nunavut Spill Report Form

NT-NU SPILL REPORT

OIL, GASOLINE, CHEMICALS AND
OTHER HAZARDOUS MATERIALS



Canada



NT-NU 24-HOUR SPILL REPORT LINE

Tel: (867) 920-8130 • Email: spills@gov.nt.ca

REPORT LINE USE ONLY

A	Report Date:	MM	DD	YY	Report Time:	☐ Original Spill Report OR ☐ Update # _____ to the Original Spill Report	Report Number:
	Occurrence Date:	MM	DD	YY	Occurrence Time:		
C	Land Use Permit Number (if applicable):				Water Licence Number (if applicable):		
D	Geographic Place Name or Distance and Direction from the Named Location:					Region: ☐ NT ☐ Nunavut ☐ Adjacent Jurisdiction or Ocean	
E	Latitude:				Longitude:		
	_____ Degrees _____ Minutes _____ Seconds				_____ Degrees _____ Minutes _____ Seconds		
F	Responsible Party or Vessel Name:				Responsible Party Address or Office Location:		
G	Any Contractor Involved:				Contractor Address or Office Location:		
H	Product Spilled: ☐ Potential Spill		Quantity in Litres, Kilograms or Cubic Metres:		U.N. Number:		
I	Spill Source:		Spill Cause:		Area of Contamination in Square Metres:		
J	Factors Affecting Spill or Recovery:		Describe Any Assistance Required:		Hazards to Persons, Property or Environment:		
K	Additional Information, Comments, Actions Proposed or Taken to Contain, Recover or Dispose of Spilled Product and Contaminated Materials:						
L	Reported to Spill Line by:		Position:	Employer:	Location Calling From:	Telephone:	
M	Any Alternate Contact:		Position:	Employer:	Alternate Contact Location:	Alternate Telephone:	

REPORT LINE USE ONLY

N	Received at Spill Line by:	Position:	Employer:	Location Called:	Report Line Number:
Lead Agency: ☐ EC ☐ CCG/TCMSS ☐ GNWT ☐ GN ☐ ILA ☐ AANDC ☐ NEB ☐ Other: _____			Significance: ☐ Minor ☐ Major ☐ Unknown		File Status: ☐ Open ☐ Closed
Agency:		Contact Name:	Contact Time:	Remarks:	
Lead Agency:					
First Support Agency:					
Second Support Agency:					
Third Support Agency:					

Appendix D

Safety Data Sheets

SAFETY DATA SHEET



DIESEL FUEL

SDS Number: 000003000395

Version: 8.1

Revision Date: 2025/03/13

Print Date: 2025/03/14

SECTION 1. IDENTIFICATION

- Product name : DIESEL FUEL
- Product code : 12163, 12162, 12161, 12160, 10582, 11803, 11802, 11798, 12016, 11958, 11796, 11771, 11770, 11769, 11768, 11767, 11766, 11612, 11560, 11558, 11555, 11437, 11302, 10979, 10978, 10977, 10976, 10975, 10974, 10973, 10972, 10971, 10970, 10969, 10968, 10966, 10965, 10964, 10786, 10785, 10784, 10783, 10690, 10689, 10687, 10636, 10635, 10626, 10621, 10616, 10610, 10601, 10600, 10598, 10595, 10427, 10041
- Other means of identification : Seasonal Diesel, #2 Diesel, #1 Diesel, #2 Heating Oil, #1 Heating Oil, OSX, D50, Arctic Diesel, Farm Diesel, Marine Diesel, Low Sulphur Diesel, LSD, Ultra Low Sulphur Diesel, ULSD, Mining Diesel, Naval Distillate, Dyed Diesel, Marked Diesel, Coloured Diesel, Furnace special, Biodiesel blend (BX where X is representative of volume %), Renewable Diesel blend (RX where X is representative of volume %), Diesel Low Cloud (LC), Marine Gas Oil, Marine Gas Oil Dyed, Type A Diesel, Type B Diesel.

Manufacturer or supplier's details

- Company name of supplier : Petro-Canada
- Address : P.O. Box 2844, 150 - 6th Avenue South-West
Calgary, Alberta T2P 3E3
Canada, Telephone: 1-866-786-2671
- Emergency telephone : CHEMTREC: 1-800-424-9300 (toll free) or +1 703-527-3887;
Suncor Energy: +1 403-296-3000

Recommended use of the chemical and restrictions on use

- Recommended use : Diesel fuels are distillate fuels suitable for use in high and medium speed internal combustion engines of the compression ignition type.
Mining diesels, marine diesels, marine diesel oil, marine gas oil and naval distillates may have a higher flash point requirement.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

- Flammable liquids : Category 3
- Acute toxicity (Inhalation) : Category 4

SAFETY DATA SHEET



DIESEL FUEL

SDS Number: 000003000395

Version: 8.1

Revision Date: 2025/03/13

Print Date: 2025/03/14

Skin irritation	: Category 2
Eye irritation	: Category 2B
Carcinogenicity	: Category 2
Specific target organ toxicity - repeated exposure	: Category 2 (Liver, thymus, Bone)
Aspiration hazard	: Category 1

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H315 + H320 Causes skin and eye irritation.
H332 Harmful if inhaled.
H351 Suspected of causing cancer.
H373 May cause damage to organs (Liver, thymus, Bone) through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe mist or vapors.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air

SAFETY DATA SHEET



DIESEL FUEL

SDS Number: 000003000395

Version: 8.1

Revision Date: 2025/03/13

Print Date: 2025/03/14

and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Fuels, diesel; Gasoil — unspecified	Fuels, diesel; Gasoil — unspecified	68334-30-5	25 - 100
Alkanes, C10-20-branched and linear	Alkanes, C10-20-branched and linear	928771-01-1	<= 75
Fatty acids, C14-18 and C14-18-unsatd., Me esters	Fatty acids, C14-18 and C14-18-unsatd., Me esters	129756-24-7	<= 20
Fuel oil No. 2	Fuel oil No. 2	68476-30-2	<= 0.2

SECTION 4. FIRST AID MEASURES

If inhaled : Move to fresh air.
Artificial respiration and/or oxygen may be necessary.
Seek medical advice.

SAFETY DATA SHEET



DIESEL FUEL

SDS Number: 000003000395

Version: 8.1

Revision Date: 2025/03/13

Print Date: 2025/03/14

In case of skin contact	: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash clothing before reuse. Seek medical advice.
In case of eye contact	: Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Obtain medical attention.
If swallowed	: Rinse mouth with water. DO NOT induce vomiting unless directed to do so by a physician or poison control center. Never give anything by mouth to an unconscious person. Seek medical advice.
Most important symptoms and effects, both acute and delayed	: Harmful if inhaled. Respiratory, skin and eye irritation; nausea; cancer.
An indication of immediate medical attention and special treatment needed, if necessary	: Treat symptomatically. For specialist advice physicians should contact the Poisons Information Service.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: Dry chemical Carbon dioxide (CO ₂) Water fog. Foam
Unsuitable extinguishing media	: Do NOT use water jet.
Specific hazards during fire fighting	: Cool closed containers exposed to fire with water spray.
Hazardous combustion products	: Carbon oxides (CO, CO ₂), nitrogen oxides (NO _x), sulphur oxides (SO _x), smoke and irritating vapours as products of incomplete combustion.
Further information	: Prevent fire extinguishing water from contaminating surface water or the ground water system.
Special protective equipment for fire-fighters	: Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: For personal protection see section 8. Ensure adequate ventilation. Evacuate personnel to safe areas.
---	---

SAFETY DATA SHEET



DIESEL FUEL

SDS Number: 000003000395

Version: 8.1

Revision Date: 2025/03/13

Print Date: 2025/03/14

Material can create slippery conditions.
Mark the contaminated area with signs and prevent access to unauthorized personnel.
Only qualified personnel equipped with suitable protective equipment may intervene.

Environmental precautions : If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Prevent further leakage or spillage if safe to do so.
Remove all sources of ignition.
Soak up with inert absorbent material.
Non-sparking tools should be used.
Ensure adequate ventilation.
Contact the proper local authorities.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Use only with adequate ventilation.
In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity.
Avoid contact with skin, eyes and clothing.
Do not ingest.
Keep away from heat and sources of ignition.
Keep container closed when not in use.

Conditions for safe storage : Store in original container.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Keep in a dry, cool and well-ventilated place.
Keep in properly labeled containers.
To maintain product quality, do not store in heat or direct sunlight.
Ensure the storage containers are grounded/bonded.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Fuels, diesel; Gasoil — unspecified	68334-30-5	TWA	100 mg/m ³ (total hydrocarbons)	CA AB OEL
		TWA (inhal-	100 mg/m ³	CA BC OEL

SAFETY DATA SHEET



DIESEL FUEL

SDS Number: 000003000395

Version: 8.1

Revision Date: 2025/03/13

Print Date: 2025/03/14

		able fraction and vapour)	(total hydrocarbons)	
		TWAEV (inhalable fraction and vapour)	100 mg/m ³ (total hydrocarbons)	CA QC OEL
		TWA (Inhalable fraction and vapor)	100 mg/m ³ (total hydrocarbons)	ACGIH
Fuel oil No. 2	68476-30-2	TWA (Inhalable fraction and vapor)	100 mg/m ³ (total hydrocarbons)	CA AB OEL
		TWA (Inhalable fraction and vapor)	100 mg/m ³ (total hydrocarbons)	CA BC OEL
		TWAEV (Inhalable fraction and vapor)	100 mg/m ³ (total hydrocarbons)	CA QC OEL
		TWA (Inhalable fraction and vapor)	100 mg/m ³ (total hydrocarbons)	CA ON OEL
		TWA (Inhalable fraction and vapor)	100 mg/m ³ (total hydrocarbons)	ACGIH

Engineering measures : Adequate ventilation to ensure that Occupational Exposure Limits are not exceeded.
Use only in well-ventilated areas.
Ensure that eyewash station and safety shower are proximal to the work-station location.

Personal protective equipment

Respiratory protection : Concentration in air determines protection needed.
Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Filter type : organic vapour cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air-purifying respirators is limited. Use a positive-pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstances where air-purifying respirators may not provide adequate protection.

Hand protection
Material : neoprene, nitrile, polyvinyl alcohol (PVA), Viton(R). Consult your PPE provider for breakthrough times and the specific glove that is best for you based on your use patterns. It should be realized that eventually any material regardless of

SAFETY DATA SHEET



DIESEL FUEL

SDS Number: 000003000395

Version: 8.1

Revision Date: 2025/03/13

Print Date: 2025/03/14

their imperviousness, will get permeated by chemicals. Therefore, protective gloves should be regularly checked for wear and tear. At the first signs of hardening and cracks, they should be changed.

Remarks	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Eye protection	: Wear safety glasses with side shields or goggles. Wear face-shield if splashing hazard is likely. Chemical splash goggles and a full-face shield should be worn when handling this material.
Skin and body protection	: Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
Protective measures	: Wash contaminated clothing before re-use.
Hygiene measures	: Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash face, hands and any exposed skin thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: Bright oily liquid.
Color	: Clear to yellow (This product may be dyed red for taxation purposes)
Odor	: Mild petroleum oil like.
pH	: No data available
Melting point and freezing point	: No data available
Boiling point, or initial boiling point and boiling range	: 150 - 371 °C
Flash point	: > 40 °C Method: closed cup Marine Gas Oil/Naval Distillate: 60°C min Mining Diesel: 52°C min All other Diesel fuels: 40°C min
Flammability	: Flammable liquid
Upper explosion limit / Upper flammability limit	: 6 %(V)

SAFETY DATA SHEET



DIESEL FUEL

SDS Number: 000003000395

Version: 8.1

Revision Date: 2025/03/13

Print Date: 2025/03/14

Lower explosion limit / Lower flammability limit	: 0.7 %(V)
Vapor pressure	: 7.5 mmHg (20 °C)
Relative vapor density	: 4.5
Relative density	: 0.8 - 0.88
Density	: No data available
Solubility(ies)	
Water solubility	: insoluble
Partition coefficient: n-octanol/water	: No data available
Autoignition temperature	: 204 °C
Decomposition temperature	: No data available
Viscosity	
Viscosity, kinematic	: 1.3 - 4.1 cSt (40 °C)
Particle characteristics	
Particle size	: Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable at normal ambient temperature and pressure.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Hazardous polymerization does not occur.
Conditions to avoid	: Extremes of temperature and direct sunlight.
Incompatible materials	: Reactive with oxidising agents and acids.
Hazardous decomposition products	: May release COx, NOx, SOx, smoke and irritating vapours when heated to decomposition.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Eye contact
Ingestion
Inhalation
Skin contact

Acute toxicity

Harmful if inhaled.

Product:

SAFETY DATA SHEET



DIESEL FUEL

SDS Number: 000003000395

Version: 8.1

Revision Date: 2025/03/13

Print Date: 2025/03/14

Acute oral toxicity	:	Remarks: Based on available data, the classification criteria are not met.
Acute inhalation toxicity	:	Acute toxicity estimate: 11 mg/L Exposure time: 4 h Test atmosphere: vapor Method: Calculation method
Acute dermal toxicity	:	Remarks: Based on available data, the classification criteria are not met.

Components:

Fuels, diesel; Gasoil — unspecified:

Acute oral toxicity	:	LD50 (Rat): 7,500 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 4.1 mg/l Exposure time: 4 h Test atmosphere: vapor
Acute dermal toxicity	:	LD50 (Mouse): 24,500 mg/kg

Fuel oil No. 2:

Acute oral toxicity	:	LD50 (Rat): 12,000 mg/kg
---------------------	---	--------------------------

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes eye irritation.

Respiratory or skin sensitization

Skin sensitization

Based on available data, the classification criteria are not met.

Respiratory sensitization

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs (Liver, thymus, Bone) through prolonged or repeated exposure.

SAFETY DATA SHEET



DIESEL FUEL

SDS Number: 000003000395

Version: 8.1

Revision Date: 2025/03/13

Print Date: 2025/03/14

Aspiration toxicity

May be fatal if swallowed and enters airways.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae/aquatic plants : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Offer surplus and non-recyclable solutions to a licensed disposal company.
Waste must be classified and labeled prior to recycling or disposal.
Send to a licensed waste management company.
Dispose of as hazardous waste in compliance with local and national regulations.
Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.

Contaminated packaging : Contact local or business unit authorities for guidance on disposal of product.

SAFETY DATA SHEET



DIESEL FUEL

SDS Number: 000003000395

Version: 8.1

Revision Date: 2025/03/13

Print Date: 2025/03/14

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 1202
Proper shipping name : Diesel fuel
Class : 3
Packing group : III
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 366

IMDG-Code

UN number : UN 1202
Proper shipping name : DIESEL FUEL
Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

UN number : UN 1202
Proper shipping name : DIESEL FUEL
Class : 3
Packing group : III
Labels : 3
ERG Code : 128
Marine pollutant : yes

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

NPRI Components : Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified
naphthalene
1,2,4-trimethylbenzene
toluene
propan-2-ol
methanol

The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

SAFETY DATA SHEET



DIESEL FUEL

SDS Number: 000003000395

Version: 8.1

Revision Date: 2025/03/13

Print Date: 2025/03/14

Canadian lists

No substances are subject to a Significant New Activity Notification.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA ON OEL	:	Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour time weighted average
CA AB OEL / TWA	:	8-hour time weighted average
CA BC OEL / TWA	:	8-hour time weighted average
CA ON OEL / TWA	:	8-hour time weighted average
CA QC OEL / TWAEV	:	Time-weighted average exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recom-

SAFETY DATA SHEET



DIESEL FUEL

SDS Number: 000003000395

Version: 8.1

Revision Date: 2025/03/13

Print Date: 2025/03/14

mendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 2025/03/13

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN

SAFETY DATA SHEET



JET A/A-1 AVIATION TURBINE FUEL

SDS Number: 000003001081

Version: 5.0

Revision Date: 2024/10/09

Print Date: 2024/10/12

SECTION 1. IDENTIFICATION

Product name : JET A/A-1 AVIATION TURBINE FUEL

Product code : 11028, 10093

Other means of identification : Jet A-1; Jet A-1-DI; Aviation Turbine Kerosene (ATK); Aviation Turbine Fuel

Manufacturer or supplier's details

Company name of supplier : SUNCOR ENERGY INC.

Address : P.O. Box 2844, 150 - 6th Avenue South-West
Calgary, Alberta T2P 3E3
Canada, Telephone: 1-866-786-2671

Emergency telephone : CHEMTREC: 1-800-424-9300 (toll free) or +1 703-527-3887;
Suncor Energy: +1 403-296-3000

Recommended use of the chemical and restrictions on use

Recommended use : Used as aviation turbine fuel. May contain a fuel system icing inhibitor. In the arctic, Jet A-1 may also be used as diesel fuel (if it contains a lubricity additive) and heating oil.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Flammable liquids : Category 3

Skin irritation : Category 2

Reproductive toxicity : Category 2

Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :



SAFETY DATA SHEET



JET A/A-1 AVIATION TURBINE FUEL

SDS Number: 000003001081

Version: 5.0

Revision Date: 2024/10/09

Print Date: 2024/10/12

Signal Word	: Danger
Hazard Statements	: H226 Flammable liquid and vapor. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H361 Suspected of damaging fertility or the unborn child.
Precautionary Statements	: Prevention: P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment. P242 Use non-sparking tools. P243 Take action to prevent static discharges. P261 Avoid breathing mist or vapors. P264 Wash skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection. Response: P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. P308 + P313 IF exposed or concerned: Get medical advice/ attention. P331 Do NOT induce vomiting. P332 + P313 If skin irritation occurs: Get medical advice/ attention. P362 + P364 Take off contaminated clothing and wash it before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. Storage: P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up. Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

SAFETY DATA SHEET



JET A/A-1 AVIATION TURBINE FUEL

SDS Number: 000003001081

Version: 5.0

Revision Date: 2024/10/09

Print Date: 2024/10/12

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Kerosine (petroleum); Straight run kerosine	Kerosine (petroleum); Straight run kerosine	8008-20-6	99.9
2-(2-methoxyethoxy)ethanol	2-(2-methoxyethoxy)ethanol	111-77-3	<= 0.15

SECTION 4. FIRST AID MEASURES

- If inhaled : Move to fresh air.
Artificial respiration and/or oxygen may be necessary.
Seek medical advice.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Wash skin thoroughly with soap and water or use recognized skin cleanser.
Wash clothing before reuse.
Seek medical advice.
- In case of eye contact : Remove contact lenses.
Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Obtain medical attention.
- If swallowed : Rinse mouth with water.
DO NOT induce vomiting unless directed to do so by a physician or poison control center.
Never give anything by mouth to an unconscious person.
Seek medical advice.
- Most important symptoms and effects, both acute and delayed : Inhalation may cause central nervous system effects.
Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.
Causes skin irritation.
Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

JET A/A-1 AVIATION TURBINE FUEL

SDS Number: 000003001081

Version: 5.0

Revision Date: 2024/10/09

Print Date: 2024/10/12

An indication of immediate medical attention and special treatment needed, if necessary : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Dry chemical
Carbon dioxide (CO₂)
Water fog.
Foam

Unsuitable extinguishing media : Do NOT use water jet.

Specific hazards during fire fighting : Cool closed containers exposed to fire with water spray.

Hazardous combustion products : Carbon oxides (CO, CO₂), nitrogen oxides (NO_x), sulphur oxides (SO_x), hydrogen sulphide (H₂S), hydrocarbons, smoke and irritating vapours as products of incomplete combustion.

Further information : Prevent fire extinguishing water from contaminating surface water or the ground water system.

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : For personal protection see section 8.
Ensure adequate ventilation.
Evacuate personnel to safe areas.
Material can create slippery conditions.
Mark the contaminated area with signs and prevent access to unauthorized personnel.
Only qualified personnel equipped with suitable protective equipment may intervene.

Environmental precautions : If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Prevent further leakage or spillage if safe to do so.
Remove all sources of ignition.

SAFETY DATA SHEET



JET A/A-1 AVIATION TURBINE FUEL

SDS Number: 000003001081

Version: 5.0

Revision Date: 2024/10/09

Print Date: 2024/10/12

Soak up with inert absorbent material.
Non-sparking tools should be used.
Ensure adequate ventilation.
Contact the proper local authorities.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Use only with adequate ventilation.
In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity.
Avoid contact with skin, eyes and clothing.
Do not ingest.
Keep away from heat and sources of ignition.
Keep container closed when not in use.
- Conditions for safe storage : Store in original container.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Keep in a dry, cool and well-ventilated place.
Keep in properly labeled containers.
To maintain product quality, do not store in heat or direct sunlight.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

- Engineering measures : Adequate ventilation to ensure that Occupational Exposure Limits are not exceeded.
Use only in well-ventilated areas.
Ensure that eyewash station and safety shower are proximal to the work-station location.

Personal protective equipment

- Respiratory protection : Concentration in air determines protection needed.
Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

- Filter type : A NIOSH-approved air-purifying respirator with an organic

JET A/A-1 AVIATION TURBINE FUEL

SDS Number: 000003001081

Version: 5.0

Revision Date: 2024/10/09

Print Date: 2024/10/12

vapour cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air-purifying respirators is limited. Use a positive-pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstances where air-purifying respirators may not provide adequate protection.

Hand protection

Material

: polyvinyl alcohol (PVA), Viton(R). Consult your PPE provider for breakthrough times and the specific glove that is best for you based on your use patterns. It should be realized that eventually any material regardless of their imperviousness, will get permeated by chemicals. Therefore, protective gloves should be regularly checked for wear and tear. At the first signs of hardening and cracks, they should be changed.

Remarks

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eye protection

: Tightly fitting safety goggles

Skin and body protection

: Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Protective measures

: Wash contaminated clothing before re-use.

Hygiene measures

: Remove and wash contaminated clothing and gloves, including the inside, before re-use.
Wash face, hands and any exposed skin thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state

: Clear liquid.

Color

: Clear and colourless

Odor

: Kerosene-like.

pH

: No data available

Melting point and freezing point

: -51 °C

SAFETY DATA SHEET



JET A/A-1 AVIATION TURBINE FUEL

SDS Number: 000003001081

Version: 5.0

Revision Date: 2024/10/09

Print Date: 2024/10/12

Boiling point, or initial boiling point and boiling range	: 140 - 300 °C
Flash point	: > 38 °C
	Method: Tagliabue
Flammability	: Flammable liquid
Upper explosion limit / Upper flammability limit	: 5 %(V)
Lower explosion limit / Lower flammability limit	: 0.7 %(V)
Vapor pressure	: 5.25 mmHg (20 °C)
Relative vapor density	: 4.5
Relative density	: 0.775 - 0.84 (15 °C)
Density	: No data available
Solubility(ies)	
Water solubility	: No data available
Partition coefficient: n-octanol/water	: No data available
Autoignition temperature	: 210 °C
Decomposition temperature	: No data available
Viscosity	
Viscosity, kinematic	: 1.0 - 1.9 cSt (40 °C)
Particle characteristics	
Particle size	: Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Hazardous polymerization does not occur.

SAFETY DATA SHEET



JET A/A-1 AVIATION TURBINE FUEL

SDS Number: 000003001081

Version: 5.0

Revision Date: 2024/10/09

Print Date: 2024/10/12

Conditions to avoid	: Extremes of temperature and direct sunlight.
Incompatible materials	: Reactive with oxidising agents, acids, alkalis, metals and halogenated compounds.
Hazardous decomposition products	: May release CO _x , NO _x , SO _x , smoke and irritating vapours when heated to decomposition.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Eye contact
Ingestion
Inhalation
Skin contact

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

Acute inhalation toxicity	: Acute toxicity estimate: > 5 mg/L Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method
Acute dermal toxicity	: Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method

Components:

Kerosine (petroleum); Straight run kerosine:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): > 5 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	: LD50 (Rabbit): > 2,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

Skin sensitization

Based on available data, the classification criteria are not met.

SAFETY DATA SHEET



JET A/A-1 AVIATION TURBINE FUEL

SDS Number: 000003001081

Version: 5.0

Revision Date: 2024/10/09

Print Date: 2024/10/12

Respiratory sensitization

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration toxicity

May be fatal if swallowed and enters airways.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae/aquatic plants : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

JET A/A-1 AVIATION TURBINE FUEL

SDS Number: 000003001081

Version: 5.0

Revision Date: 2024/10/09

Print Date: 2024/10/12

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

- Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Offer surplus and non-recyclable solutions to a licensed disposal company.
Waste must be classified and labeled prior to recycling or disposal.
Send to a licensed waste management company.
Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.
- Contaminated packaging : Do not re-use empty containers.
Contact local or business unit authorities for guidance on disposal of product.

SECTION 14. TRANSPORT INFORMATION**International Regulations****IATA-DGR**

- UN/ID No. : UN 1863
Proper shipping name : Fuel, aviation, turbine engine
Class : 3
Packing group : III
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 366

IMDG-Code

- UN number : UN 1863
Proper shipping name : FUEL, AVIATION, TURBINE ENGINE
- Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**TDG**

- UN number : UN 1863
Proper shipping name : FUEL, AVIATION, TURBINE ENGINE
- Class : 3
Packing group : III
Labels : 3

SAFETY DATA SHEET



JET A/A-1 AVIATION TURBINE FUEL

SDS Number: 000003001081

Version: 5.0

Revision Date: 2024/10/09

Print Date: 2024/10/12

ERG Code : 128
Marine pollutant : yes

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

NPRI Components : 2-(2-methoxyethoxy)ethanol
toluene
Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified
naphthalene
propan-2-ol
methanol

The ingredients of this product are reported in the following inventories:

TCSI : On the inventory, or in compliance with the inventory
TSCA : All substances listed as active on the TSCA inventory
DSL : All components of this product are on the Canadian DSL
KECI : On the inventory, or in compliance with the inventory
PICCS : On the inventory, or in compliance with the inventory
IECSC : On the inventory, or in compliance with the inventory

Canadian lists

The following substance(s) is/are subject to a Significant New Activity Notification:
2-(2-methoxyethoxy)ethanol 111-77-3

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory con-

SAFETY DATA SHEET



JET A/A-1 AVIATION TURBINE FUEL

SDS Number: 000003001081

Version: 5.0

Revision Date: 2024/10/09

Print Date: 2024/10/12

centration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 2024/10/09

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN

SAFETY DATA SHEET

{ error: graphic
file not found:
E:\WWI\graphics

GASOLINE, UNLEADED

SDS Number: 000003000644

Version: 5.0

Revision Date: 2025/02/05

Print Date: 2025/02/13

SECTION 1. IDENTIFICATION

Product name : GASOLINE, UNLEADED

Product code : 11949, 11000, 10999, 10998, 10995, 10993, 10991, 10990, 10989, 10988, 10987, 10474, 10473, 10461, 10455, 10111, 10108, 10097, 10096, 10040, 10039

Other means of identification : LVB87, Regular, Unleaded Gasoline (US Grade), Mid-Grade, Plus, Super, Supreme, SuperClean, RegularClean, Plus-Clean, Premium, marked or dyed gasoline, BOB, Blendstock for Oxygenate Blending, Conventional Gasoline, RUL, MUL, SUL, PUL, Additive Denaturant, LVBU (low volatility blend ultra), LVBR (low volatility blend regular).

Manufacturer or supplier's details

Company name of supplier : Petro-Canada
Address : P.O. Box 2844, 150 - 6th Avenue South-West
Calgary, Alberta T2P 3E3
Canada, Telephone: 1-866-786-2671

Emergency telephone : CHEMTREC: 1-800-424-9300 (toll free) or +1 703-527-3887;
^CR^Suncor Energy: +1 403-296-3000

Recommended use of the chemical and restrictions on use

Recommended use : Unleaded gasoline is used in spark ignition engines including motor vehicles, inboard and outboard boat engines, small engines such as chain saws and lawn mowers, and recreational vehicles.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Flammable liquids : Category 1

Skin irritation : Category 2

Germ cell mutagenicity : Category 1B

Carcinogenicity : Category 1A

Reproductive toxicity : Category 2

Specific target organ toxicity : Category 3 (Central nervous system)
- single exposure

Specific target organ toxicity : Category 1 (hematopoietic system)
- repeated exposure (Inhalation)

SAFETY DATA SHEET

{ error: graphic
file not found:
E:\WWI\graphics

GASOLINE, UNLEADED

SDS Number: 000003000644

Version: 5.0

Revision Date: 2025/02/05

Print Date: 2025/02/13

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H224 Extremely flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H340 May cause genetic defects.
H350 May cause cancer.
H361 Suspected of damaging fertility or the unborn child.
H372 Causes damage to organs (hematopoietic system) through prolonged or repeated exposure if inhaled.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe mist or vapors.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P331 Do NOT induce vomiting.

SAFETY DATA SHEET

{ error: graphic
file not found:
E:\WWI\graphics

GASOLINE, UNLEADED

SDS Number: 000003000644

Version: 5.0

Revision Date: 2025/02/05

Print Date: 2025/02/13

P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Gasoline; Low boiling point naphtha - unspecified	Gasoline; Low boiling point naphtha - unspecified	86290-81-5	80 - 100
toluene	toluene	108-88-3	<= 40
benzene	benzene	71-43-2	0.006 - 1.5
ethanol	ethanol	64-17-5	<= 0.3
methanol	methanol	67-56-1	<= 0.08

SECTION 4. FIRST AID MEASURES

If inhaled : Move to fresh air.
Artificial respiration and/or oxygen may be necessary.
Seek medical advice.

In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Wash skin thoroughly with soap and water or use recognized skin cleanser.
Wash clothing before reuse.
Seek medical advice.

In case of eye contact : Remove contact lenses.
Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Obtain medical attention.

SAFETY DATA SHEET

{ error: graphic
file not found:
E:\WWI\graphics

GASOLINE, UNLEADED

SDS Number: 000003000644

Version: 5.0

Revision Date: 2025/02/05

Print Date: 2025/02/13

If swallowed	: Rinse mouth with water. DO NOT induce vomiting unless directed to do so by a physician or poison control center. Never give anything by mouth to an unconscious person. Seek medical advice.
Most important symptoms and effects, both acute and delayed	: Respiratory, skin and eye irritation; nausea; cancer. Inhalation may cause central nervous system effects. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Chronic exposure to benzene may result in increased risk of leukemia and other blood disorders.
An indication of immediate medical attention and special treatment needed, if necessary	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: Dry chemical Carbon dioxide (CO ₂) Water fog. Foam
Unsuitable extinguishing media	: Do NOT use water jet.
Specific hazards during fire fighting	: Cool closed containers exposed to fire with water spray.
Hazardous combustion products	: Carbon oxides (CO, CO ₂), nitrogen oxides (NO _x), polynuclear aromatic hydrocarbons, phenols, aldehydes, ketones, smoke and irritating vapours as products of incomplete combustion.
Further information	: Prevent fire extinguishing water from contaminating surface water or the ground water system.
Special protective equipment for fire-fighters	: Wear self-contained breathing apparatus and full protective wear. Wear a positive-pressure supplied-air respirator with full face-piece.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: For personal protection see section 8. Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions. Mark the contaminated area with signs and prevent access to unauthorized personnel. Only qualified personnel equipped with suitable protective equipment may intervene.
---	---

SAFETY DATA SHEET

{ error: graphic
file not found:
E:\WWI\graphics

GASOLINE, UNLEADED

SDS Number: 000003000644

Version: 5.0

Revision Date: 2025/02/05

Print Date: 2025/02/13

Environmental precautions : If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Prevent further leakage or spillage if safe to do so.
Remove all sources of ignition.
Soak up with inert absorbent material.
Non-sparking tools should be used.
Ensure adequate ventilation.
Contact the proper local authorities.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Use only with adequate ventilation.
In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity.
Avoid contact with skin, eyes and clothing.
Do not ingest.
Keep away from heat and sources of ignition.
Keep container closed when not in use.

Conditions for safe storage : Store in original container.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Keep in a dry, cool and well-ventilated place.
Keep in properly labeled containers.
To maintain product quality, do not store in heat or direct sunlight.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Gasoline; Low boiling point naphtha -unspecified	86290-81-5	TWA	300 ppm	CA AB OEL
		STEL	500 ppm	CA AB OEL
		TWA	300 ppm	CA BC OEL
		STEL	500 ppm	CA BC OEL
		TWA	300 ppm	ACGIH
		STEL	500 ppm	ACGIH
toluene	108-88-3	TWA	20 ppm	CA BC OEL
		TWAEV	20 ppm	CA QC OEL
		TWA	50 ppm	CA AB OEL
		TWA	20 ppm	ACGIH

SAFETY DATA SHEET

{ error: graphic
file not found:
E:\WWI\graphics

GASOLINE, UNLEADED

SDS Number: 000003000644

Version: 5.0

Revision Date: 2025/02/05

Print Date: 2025/02/13

benzene	71-43-2	TWA	0.5 ppm	CA BC OEL
		STEL	2.5 ppm	CA BC OEL
		TWA	0.5 ppm	CA ON OEL
		STEL	2.5 ppm	CA ON OEL
		TWAEV	0.5 ppm	CA QC OEL
		STEV	2.5 ppm	CA QC OEL
		TWA	0.5 ppm	CA AB OEL
		STEL	2.5 ppm	CA AB OEL
		TWA	0.02 ppm	ACGIH
		STEL	0.1 ppm	ACGIH
ethanol	64-17-5	STEL	1,000 ppm	CA BC OEL
		STEV	1,000 ppm	CA QC OEL
		TWA	300 ppm	CA AB OEL
		STEL	500 ppm	CA AB OEL
		STEL	1,000 ppm	ACGIH
methanol	67-56-1	TWA	200 ppm	CA BC OEL
		STEL	250 ppm	CA BC OEL
		TWA	200 ppm	CA AB OEL
		STEL	250 ppm	CA AB OEL
		TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH

Engineering measures : Adequate ventilation to ensure that Occupational Exposure Limits are not exceeded.
Use only in well-ventilated areas.
Ensure that eyewash station and safety shower are proximal to the work-station location.

Personal protective equipment

Respiratory protection : Concentration in air determines protection needed.
Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Filter type : A NIOSH-approved air-purifying respirator with an organic vapour cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air-purifying respirators is limited. Use a positive-pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstances where air-purifying respirators may not provide adequate protection.

Hand protection
Material : polyvinyl alcohol (PVA), Viton(R). Consult your PPE provider for breakthrough times and the specific glove that is best for you based on your use patterns. It should be realized that eventually any material regardless of their imperviousness, will get permeated by chemicals. Therefore, protective gloves should be regularly checked for wear and tear. At the first

SAFETY DATA SHEET

{ error: graphic
file not found:
E:\WWI\graphics

GASOLINE, UNLEADED

SDS Number: 000003000644

Version: 5.0

Revision Date: 2025/02/05

Print Date: 2025/02/13

	signs of hardening and cracks, they should be changed.
Remarks	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Eye protection	: Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection	: Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
Protective measures	: Wash contaminated clothing before re-use.
Hygiene measures	: Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash face, hands and any exposed skin thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: Clear liquid.
Color	: Clear to slightly yellow or green, undyed liquid. May be dyed red for taxation purposes.
Odor	: Gasoline
pH	: No data available
Melting point and freezing point	: No data available
Boiling point, or initial boiling point and boiling range	: 25 - 225 °C
Flash point	: -50 - -38 °C Method: Tagliabue.
Flammability	: Extremely flammable in presence of open flames and sparks. May accumulate static electrical charge. Vapours are heavier than air and may travel considerable distance to sources of ignition and flash back.
Upper explosion limit / Upper flammability limit	: 7.6 %(V)
Lower explosion limit / Lower flammability limit	: 1.3 %(V)
Vapor pressure	: < 802.5 mmHg (20 °C)
Relative vapor density	: 3

SAFETY DATA SHEET

{ error: graphic
file not found:
E:\WWI\graphics

GASOLINE, UNLEADED

SDS Number: 000003000644

Version: 5.0

Revision Date: 2025/02/05

Print Date: 2025/02/13

Relative density	:	0.685 - 0.8
Density	:	No data available
Solubility(ies)		
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	257 °C
Decomposition temperature	:	No data available
Viscosity		
Viscosity, kinematic	:	No data available
Particle characteristics		
Particle size	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Hazardous polymerization does not occur.
Conditions to avoid	:	Extremes of temperature and direct sunlight.
Incompatible materials	:	Reactive with oxidising agents, acids and interhalogens.
Hazardous decomposition products	:	May release COx, NOx, phenols, polycyclic aromatic hydrocarbons, aldehydes, ketones, smoke and irritating vapours when heated to decomposition.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Eye contact
Ingestion
Inhalation
Skin contact

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

Acute oral toxicity	:	Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: > 20 mg/L Exposure time: 4 h Test atmosphere: vapor Method: Calculation method

SAFETY DATA SHEET

{ error: graphic
file not found:
E:\WWI\graphics

GASOLINE, UNLEADED

SDS Number: 000003000644

Version: 5.0

Revision Date: 2025/02/05

Print Date: 2025/02/13

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:

Gasoline; Low boiling point naphtha -unspecified:

Acute oral toxicity : LD50 (Rat): 13,600 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 3,750 mg/kg

toluene:

Acute oral toxicity : LD50 (Rat): 5,580 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): 12,125 mg/kg

benzene:

Acute oral toxicity : LD50 (Rat): 2,990 mg/kg

Acute inhalation toxicity : LC50 (Rat): 13700 ppm
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 8,240 mg/kg

ethanol:

Acute oral toxicity : LD50 (Rat): 7,060 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 32380 ppm
Exposure time: 4 h
Test atmosphere: vapor

methanol:

Acute oral toxicity : LD50 (Rat): 5,600 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 15,800 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

{ error: graphic
file not found:
E:\WWI\graphics

GASOLINE, UNLEADED

SDS Number: 000003000644

Version: 5.0

Revision Date: 2025/02/05

Print Date: 2025/02/13

Respiratory or skin sensitization

Skin sensitization

Based on available data, the classification criteria are not met.

Respiratory sensitization

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

May cause genetic defects.

May cause cancer.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Causes damage to organs (hematopoietic system) through prolonged or repeated exposure if inhaled.

Aspiration toxicity

May be fatal if swallowed and enters airways.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other :
aquatic invertebrates Remarks: No data available

Toxicity to algae/aquatic :
plants Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SAFETY DATA SHEET

{ error: graphic
file not found:
E:\WWI\graphics

GASOLINE, UNLEADED

SDS Number: 000003000644

Version: 5.0

Revision Date: 2025/02/05

Print Date: 2025/02/13

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Offer surplus and non-recyclable solutions to a licensed disposal company.
Waste must be classified and labeled prior to recycling or disposal.
Send to a licensed waste management company.
Dispose of as hazardous waste in compliance with local and national regulations.
Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.
- Contaminated packaging : Contact local or business unit authorities for guidance on disposal of product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

- UN/ID No. : UN 1203
Proper shipping name : Gasoline
Class : 3
Packing group : II
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 364

IMDG-Code

- UN number : UN 1203
Proper shipping name : GASOLINE
Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

- UN number : UN 1203
Proper shipping name : GASOLINE
Class : 3
Packing group : II
Labels : 3
ERG Code : 128
Marine pollutant : yes

SAFETY DATA SHEET

{ error: graphic
file not found:
E:\WWI\graphics

GASOLINE, UNLEADED

SDS Number: 000003000644

Version: 5.0

Revision Date: 2025/02/05

Print Date: 2025/02/13

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

NPRI Components : toluene
benzene
ethanol
methanol
xylene
Naphtha (petroleum), hydrotreated heavy; Low boiling point
hydrogen treated naphtha
ethylbenzene
Solvent naphtha (petroleum), heavy arom.; Kerosine — un-
specified
naphthalene
1,2,4-trimethylbenzene

The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

Canadian lists

No substances are subject to a Significant New Activity Notification.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL : Canada. British Columbia OEL
CA ON OEL : Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for air-borne contaminants
ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
CA AB OEL / STEL : Short term exposure limit
CA AB OEL / TWA : Time weighted average
CA AB OEL / TWA : 8-hour Occupational exposure limit
CA AB OEL / STEL : 15-minute occupational exposure limit
CA BC OEL / TWA : 8-hour time weighted average
CA BC OEL / STEL : short-term exposure limit
CA ON OEL / TWA : Time-Weighted Average Limit (TWA)
CA ON OEL / STEL : Short-Term Exposure Limit (STEL)
CA QC OEL / TWA EV : Time-weighted average exposure value

SAFETY DATA SHEET

{ error: graphic
file not found:
E:\WWI\graphics

GASOLINE, UNLEADED

SDS Number: 000003000644

Version: 5.0

Revision Date: 2025/02/05

Print Date: 2025/02/13

CA QC OEL / STEV : Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 2025/02/05

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN

SAFETY DATA SHEET

Version 6.8
Revision Date 01.05.2025
Print Date 02.05.2025

SECTION 1. IDENTIFICATION

1.1 Product identifiers

Product name : Kerosene

Product Number : 60710
Brand : SIGALD
Index-No. : 649-404-00-4
CAS-No. : 8008-20-6

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : MilliporeSigma Canada Ltd.
2149 WINSTON PARK DRIVE
OAKVILLE ON L6H 6J8
CANADA

Telephone : +1 905 829-9500
Fax : +1 905 829-9292

1.4 Emergency telephone

Emergency Phone # : +1-703-527-3887 CHEMTREC
(International)
24 Hours/day; 7 Days/week

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Flammable liquids : Category 4

Skin irritation : Category 2

Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

Aspiration hazard : Category 1

Long-term (chronic) aquatic hazard : Category 2

SIGALD - 60710

Page 1 of 11

GHS label elements

Hazard pictograms

:



Signal Word

: Danger

Hazard Statements

: H227 Combustible liquid.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements :

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing mist or vapors.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P302 + P352 IF ON SKIN: Wash with plenty of water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P391 Collect spillage.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Components

Chemical name	CAS-No.	Concentration (% w/w)
Kerosine	8008-20-6	$\geq 80 - \leq 100$ *

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : Show this material safety data sheet to the doctor in attendance.
- If inhaled : After inhalation: fresh air. Call in physician.
- In case of skin contact : In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.
- In case of eye contact : After eye contact: rinse out with plenty of water. Remove contact lenses.
- If swallowed : After swallowing: caution if victim vomits. Risk of aspiration! Keep airways free. Pulmonary failure possible after aspiration of vomit. Call a physician immediately.
- Most important symptoms and effects, both acute and delayed : The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11
- Protection of first-aiders : For personal protection see section 8.
- Notes to physician : No data available

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Foam
Carbon dioxide (CO₂)
Dry powder
- Unsuitable extinguishing media : For this substance/mixture no limitations of extinguishing agents are given.
- Specific hazards during : Combustible.

SIGALD - 60710

Page 3 of 11

Vapors are heavier than air and may spread along floors.

Forms explosive mixtures with air on intense heating.

Development of hazardous combustion gases or vapours possible in the event of fire.

Hazardous combustion products	: Nature of decomposition products not known.
Specific extinguishing methods	: No data available
Further information	: Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.
Special protective equipment for fire-fighters	: Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. Advice for emergency responders: For personal protection see section 8.
Environmental precautions	: Do not let product enter drains.
Methods and materials for containment and cleaning up	: Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g.

SIGALD - 60710

Page 4 of 11

Chemizorb®). Dispose of properly. Clean up affected area.

SECTION 7. HANDLING AND STORAGE

For precautions see section 2.2.

- Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition.
Take precautionary measures against static discharge.
- Advice on safe handling : Work under hood. Do not inhale substance/mixture.
Avoid generation of vapours/aerosols.
- Further information on storage conditions : Keep container tightly closed in a dry and well-ventilated place.
Keep away from heat and sources of ignition.
- Storage class : 3, Flammable liquids
- Recommended storage temperature : Recommended storage temperature see product label.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Kerosine	8008-20-6	TWA	200 mg/m ³ (total hydrocarbon vapor)	CA BC OEL
		TWA	200 mg/m ³ (total hydrocarbon vapor)	CA AB OEL
		TWAEV	200 mg/m ³	CA QC OEL
		TWA	200 mg/m ³ (total hydrocarbon vapor)	ACGIH

Engineering measures : No data available

Personal protective equipment

Respiratory protection : required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Recommended Filter type: : Filter type ABEK

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Hand protection

Remarks : required

Eye protection : Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).
Safety glasses

Skin and body protection : protective clothing

Hygiene measures : Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid, clear

Color : colorless

Odor : No data available

Odor Threshold : No data available
pH : No data available

Melting point : No data available

Boiling point/boiling range : 175 - 325 °C (1,013 hPa)

Flash point : 82 °C

Method: closed cup

Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Flammability (liquids)	: No data available
Burning rate	: No data available
Upper explosion limit / Upper flammability limit	: 5 %(V)
Lower explosion limit / Lower flammability limit	: 0.7 %(V)
Vapor pressure	: 0.31 hPa (20 °C)
Relative vapor density	: No data available
Relative density	: No data available
Density	: 0.8 g/mL (25 °C)
Water solubility	: No data available
Partition coefficient: n- octanol/water	: No data available
Autoignition temperature	: 228 °C
Decomposition temperature	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Flow time	: No data available
Explosive properties	: Not classified as explosive.
Oxidizing properties	: none
Surface tension	: 32 mN/m, 20 °C
Particle characteristics Particle size	: No data available

SECTION 10. STABILITY AND REACTIVITY

SIGALD - 60710

Page 7 of 11

The life science business of Merck KGaA, Darmstadt, Germany
operates as MilliporeSigma in the US and Canada

MILLIPORE
SIGMA

Reactivity	: Forms explosive mixtures with air on intense heating. A range from approx. 15 Kelvin below the flash point is to be rated as critical.
Chemical stability	: The product is chemically stable under standard ambient conditions (room temperature) .
Possibility of hazardous reactions	: No data available
Conditions to avoid	: Strong heating.
Incompatible materials	: Strong oxidizing agents Strong bases Strong acids Amines
Hazardous decomposition products	: In the event of fire: see section 5

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rabbit - 2,835 mg/kg

Remarks: Behavioral: Muscle weakness.

Lungs, Thorax, or Respiration: Respiratory stimulation.

Endocrine: Hypoglycemia.

Inhalation: No data available

Dermal: No data available

No data available

Skin corrosion/irritation

Skin - Rabbit

Result: Irritating to skin. - 24 h
(Draize Test)

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Inhalation - May cause drowsiness or dizziness. - Central nervous system

SIGALD - 60710

Page 8 of 11

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2 Additional Information

RTECS: OA5500000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Kerosine:**

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia): 0.48 mg/l
Exposure time: 21 d

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects**Components:****Kerosine:**

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National regulation

TDG

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

Canadian lists

No substances are subject to a Significant New Activity Notification.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA QC OEL / TWAEV	:	Time-weighted average exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization;

SIGALD - 60710

Page 10 of 11

IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

Revision Date : 01.05.2025
Date format : mm/dd/yyyy

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

CA / EN

Safety Data Sheet



SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

Clarity Hydraulic Oil AW 32, 46, 68

Product Use: Hydraulic Oil

Product Number(s): 219612, 230340, 230341, 230342, 278022, 278023, 278024

Synonyms: Clarity Hydraulic Oil AW 32 ISOCLEAN Certified; Clarity Hydraulic Oil AW 46 ISOCLEAN Certified; Clarity Hydraulic Oil AW 68 ISOCLEAN Certified

Company Identification

Chevron Products Company
a division of Chevron U.S.A. Inc.
5001 Executive Parkway
San Ramon, CA 94583
United States of America
www.chevronlubricants.com

Transportation Emergency Response

CHEMTREC: (800) 424-9300 or (703) 527-3887

Health Emergency

Chevron Emergency & Information Center: Located in the USA. International collect calls accepted. (800) 231-0623 or (510) 231-0623

Product Information

email : lubemsds@chevron.com

Product Information: 1 (800) 582-3835, LUBETEK@chevron.com

SECTION 2 HAZARDS IDENTIFICATION

CLASSIFICATION:

Not classified as hazardous according to 29 CFR 1910.1200 (2012).

HAZARDS NOT OTHERWISE CLASSIFIED: Not Applicable

SECTION 3 COMPOSITION/ INFORMATION ON INGREDIENTS

COMPONENTS	CAS NUMBER	AMOUNT
Distillates, hydrotreated heavy paraffinic	64742-54-7	70 - 99 %weight

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye: No specific first aid measures are required. As a precaution, remove contact lenses, if worn, and flush eyes with water.

Skin: No specific first aid measures are required. As a precaution, remove clothing and shoes if contaminated. To remove the material from skin, use soap and water. Discard contaminated clothing

and shoes or thoroughly clean before reuse.

Ingestion: No specific first aid measures are required. Do not induce vomiting. As a precaution, get medical advice.

Inhalation: No specific first aid measures are required. If exposed to excessive levels of material in the air, move the exposed person to fresh air. Get medical attention if coughing or respiratory discomfort occurs.

Most important symptoms and effects, both acute and delayed

IMMEDIATE HEALTH EFFECTS

Eye: Not expected to cause prolonged or significant eye irritation.

Skin: High-Pressure Equipment Information: Accidental high-velocity injection under the skin of materials of this type may result in serious injury. Seek medical attention at once should an accident like this occur. The initial wound at the injection site may not appear to be serious at first; but, if left untreated, could result in disfigurement or amputation of the affected part.

Contact with the skin is not expected to cause prolonged or significant irritation. Contact with the skin is not expected to cause an allergic skin response. Not expected to be harmful to internal organs if absorbed through the skin.

Ingestion: Not expected to be harmful if swallowed.

Inhalation: Not expected to be harmful if inhaled. Contains a petroleum-based mineral oil. May cause respiratory irritation or other pulmonary effects following prolonged or repeated inhalation of oil mist at airborne levels above the recommended mineral oil mist exposure limit. Symptoms of respiratory irritation may include coughing and difficulty breathing.

DELAYED OR OTHER HEALTH EFFECTS: Not classified

Indication of any immediate medical attention and special treatment needed

Note to Physicians: In an accident involving high-pressure equipment, this product may be injected under the skin. Such an accident may result in a small, sometimes bloodless, puncture wound.

However, because of its driving force, material injected into a fingertip can be deposited into the palm of the hand. Within 24 hours, there is usually a great deal of swelling, discoloration, and intense throbbing pain. Immediate treatment at a surgical emergency center is recommended.

SECTION 5 FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Use water fog, foam, dry chemical or carbon dioxide (CO₂) to extinguish flames.

Unusual Fire Hazards: Leaks/ruptures in high pressure system using materials of this type can create a fire hazard when in the vicinity of ignition sources (eg. open flame, pilot lights, sparks, or electric arcs).

PROTECTION OF FIRE FIGHTERS:

Fire Fighting Instructions: This material will burn although it is not easily ignited. See Section 7 for proper handling and storage. For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus.

Combustion Products: Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, and unidentified organic compounds will be evolved when this material undergoes combustion.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Protective Measures: Observe all relevant local and international regulations. Eliminate all sources of ignition in vicinity of spilled material. Keep out unnecessary and unprotected personnel. Persons entering the contaminated area to correct the problem or to determine whether it is safe to resume normal activities must comply with all instructions in the Exposure Controls/Personal Protection section.

Spill Management: Stop the source of the release if you can do it without risk. Contain release to prevent further contamination of soil, surface water or groundwater. Clean up spill as soon as possible, observing precautions in Exposure Controls/Personal Protection. Use appropriate techniques such as applying non-combustible absorbent materials or pumping. Where feasible and appropriate, remove contaminated soil. Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations.

Reporting: Report spills to local authorities and/or the U.S. Coast Guard's National Response Center at (800) 424-8802 as appropriate or required.

SECTION 7 HANDLING AND STORAGE

General Handling Information: Avoid contaminating soil or releasing this material into sewage and drainage systems and bodies of water.

Precautionary Measures: DO NOT USE IN HIGH PRESSURE SYSTEMS in the vicinity of flames, sparks and hot surfaces. Use only in well ventilated areas. Keep container closed.

Static Hazard: Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not, by themselves, be sufficient. Review all operations which have the potential of generating and accumulating an electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures.

Container Warnings: Container is not designed to contain pressure. Do not use pressure to empty container or it may rupture with explosive force. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

GENERAL CONSIDERATIONS:

Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the workplace when designing engineering controls and selecting personal protective equipment (PPE). If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, refer to PPE information below.

Factors that affect PPE include, but are not limited to: properties of the chemical, other chemicals which may contact the same PPE, physical requirements (fit & sizing, cut/puncture protection, dexterity, thermal protection, etc.), and potential allergic reactions to the PPE material. It is the responsibility of the user to read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances. Refer to appropriate CEN standards.

ENGINEERING CONTROLS:

Use in a well-ventilated area.

PERSONAL PROTECTIVE EQUIPMENT

Eye/Face Protection: Wear protective equipment to prevent eye contact. Selection of protective equipment may include safety glasses, chemical goggles, face shields, or a combination depending on the work operations conducted.

Skin Protection: Wear chemical personal protective equipment (PPE) to prevent skin contact. Selection of chemical protective clothing should be performed by an Occupational Hygienist or Safety Professional and be based upon applicable standards (ASTM F739 or EN 374). Using chemical PPE depends upon operations conducted and may include chemical gloves, boots, chemical apron, chemical suit, and

complete facial protection. **Refer to PPE manufacturers to obtain breakthrough time information to determine how long PPE can be used before it needs to be replaced.** Unless specific glove manufacturer data indicates otherwise, the below table is based upon available industry data to assist in the glove selection process and is intended to be used as reference only.

Chemical Glove Material	Thickness (mm)	Typical Breakthrough Time (minutes)
Butyl	0.7	120
Nitrile	0.8	240
Viton Butyl	0.3	240

Respiratory Protection: No respiratory protection is normally required.

If user operations generate an oil mist, determine if airborne concentrations are below the occupational exposure limit for mineral oil mist. If not, wear an approved respirator that provides adequate protection from the measured concentrations of this material. For air-purifying respirators use a particulate cartridge.

Use a positive pressure air-supplying respirator in circumstances where air-purifying respirators may not provide adequate protection.

Occupational Exposure Limits:

Component	Agency	Form	TWA	STEL	Ceiling	Notation
Distillates, hydrotreated heavy paraffinic	ACGIH	--	5 mg/m3	10 mg/m3	--	--
Distillates, hydrotreated heavy paraffinic	ACGIH	Inhalable fraction	5 mg/m3	--	--	--
Distillates, hydrotreated heavy paraffinic	OSHA Z-1	--	5 mg/m3	--	--	--
Distillates, hydrotreated heavy paraffinic	OSHA Z-1	Mist	5 mg/m3	--	--	--

Consult local authorities for appropriate values.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Attention: the data below are typical values and do not constitute a specification.

Color: Brown to yellow

Physical State: Liquid

Odor: Petroleum odor

Odor Threshold: No data available

pH: Not Applicable

Vapor Pressure: No data available

Relative Vapor Density: No data available

Initial Boiling Point: No data available

Solubility: Soluble in hydrocarbons; insoluble in water

Freezing Point: Not Applicable

Melting Point: No data available

Particle Characteristics: Not applicable

Density: 0.856 kg/l - 0.8671 kg/l @ 15°C (59°F) (Typical)

Kinematic Viscosity: 28.8 mm2/s - 74.8 mm2/s @ 40°C (104°F)

Evaporation Rate: No data available

Decomposition temperature: No data available

Partition coefficient n-octanol/water (logarithmic value): No data available

FLAMMABLE PROPERTIES:

Flammability (solid, gas): Not Applicable

Flashpoint: (Cleveland Open Cup) 200 °C (392 °F) (Minimum)

Autoignition: No data available

Flammability (Explosive) Limits (% by volume in air): Lower: Not Applicable Upper: Not Applicable

SECTION 10 STABILITY AND REACTIVITY

Reactivity: May react with strong acids or strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

Chemical Stability: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

Incompatibility With Other Materials: Not applicable

Hazardous Decomposition Products: None known (None expected)

Hazardous Polymerization: Hazardous polymerization will not occur.

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Serious Eye Damage/Irritation: The material is not considered an eye irritant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Skin Corrosion/Irritation: The material is not considered a skin irritant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Skin Sensitization: The material is not considered a skin sensitizer. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Acute Dermal Toxicity: The material is not considered a dermal toxicant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Acute Oral Toxicity: The material is not considered an oral toxicant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Acute Inhalation Toxicity: The material is not considered an inhalation toxicant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Acute Toxicity Estimate: Not Determined

Germ Cell Mutagenicity: The material is not considered a mutagen. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Carcinogenicity: The material is not considered a carcinogen. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Reproductive Toxicity: The material is not considered a reproductive toxicant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Specific Target Organ Toxicity - Single Exposure: The material is not considered a target organ toxicant (single exposure). The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Specific Target Organ Toxicity - Repeated Exposure: The material is not considered a target organ toxicant (repeated exposure). The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

Aspiration Hazard: The material is not considered an aspiration hazard.

ADDITIONAL TOXICOLOGY INFORMATION:

This product contains petroleum base oils which may be refined by various processes including severe solvent extraction, severe hydrocracking, or severe hydrotreating. None of the oils requires a cancer warning under the OSHA Hazard Communication Standard (29 CFR 1910.1200). These oils have not been listed in the National Toxicology Program (NTP) Annual Report nor have they been classified by the International Agency for Research on Cancer (IARC) as; carcinogenic to humans (Group 1), probably carcinogenic to humans (Group 2A), or possibly carcinogenic to humans (Group 2B).

These oils have not been classified by the American Conference of Governmental Industrial Hygienists (ACGIH) as: confirmed human carcinogen (A1), suspected human carcinogen (A2), or confirmed animal carcinogen with unknown relevance to humans (A3).

SECTION 12 ECOLOGICAL INFORMATION

ECOTOXICITY

This material is not expected to be harmful to aquatic organisms.

The product has not been tested. The statement has been derived from the properties of the individual components.

MOBILITY

No data available.

PERSISTENCE AND DEGRADABILITY

This material is not expected to be readily biodegradable. The product has not been tested. The statement has been derived from the properties of the individual components.

POTENTIAL TO BIOACCUMULATE

Bioconcentration Factor: No data available.

Partition coefficient n-octanol/water (logarithmic value): No data available

SECTION 13 DISPOSAL CONSIDERATIONS

Use material for its intended purpose or recycle if possible. Oil collection services are available for used oil recycling or disposal. Place contaminated materials in containers and dispose of in a manner consistent with applicable regulations. Contact your sales representative or local environmental or health authorities for approved disposal or recycling methods.

SECTION 14 TRANSPORT INFORMATION

The description shown may not apply to all shipping situations. Consult 49CFR, or appropriate Dangerous Goods Regulations, for additional description requirements (e.g., technical name) and mode-specific or quantity-specific shipping requirements.

DOT Shipping Description: NOT REGULATED AS HAZARDOUS MATERIAL UNDER 49 CFR

IMO/IMDG Shipping Description: NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT UNDER THE IMDG CODE

ICAO/IATA Shipping Description: NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT UNDER ICAO

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code:

Not applicable

SECTION 15 REGULATORY INFORMATION

EPCRA 311/312 CATEGORIES: Not applicable

REGULATORY LISTS SEARCHED:

01-1=IARC Group 1	05=MA RTK
01-2A=IARC Group 2A	06=NJ RTK
01-2B=IARC Group 2B	07=PA RTK
02=NTP Carcinogen	08-1=TSCA 5(e)
03=EPCRA 313	08-2=TSCA 12(b)
04=CA Proposition 65	

The following components of this material are found on the regulatory lists indicated.

Distillates, hydrotreated heavy paraffinic 05, 06, 07

CHEMICAL INVENTORIES:

All components comply with the following chemical inventory requirements: AIIIC (Australia), DSL (Canada), ENCS (Japan), IECSC (China), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States).

One or more components is listed on ELINCS (European Union). All other components are listed or exempted from listing on EINECS.

NEW JERSEY RTK CLASSIFICATION:

Under the New Jersey Right-to-Know Act L. 1983 Chapter 315 N.J.S.A. 34:5A-1 et. seq., the product is to be identified as follows: PETROLEUM OIL (Hydraulic oil)

SECTION 16 OTHER INFORMATION

NFPA RATINGS: Health: 0 Flammability: 1 Reactivity: 0

HMIS RATINGS: Health: 0* Flammability: 1 Reactivity: 0
(0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme, PPE:- Personal Protection Equipment Index recommendation, *- Chronic Effect Indicator). These values are obtained using the guidelines or published evaluations prepared by the National Fire Protection Association (NFPA) or the National Paint and Coating Association (for HMIS ratings).

REVISION STATEMENT:

SECTION 01 - Company SDS Address information was modified.
SECTION 01 - Product Code(s) information was modified.
SECTION 01 - Product Identifier information was modified.
SECTION 02 - Hazard Statements information was deleted.
SECTION 02 - Health Classification information was deleted.
SECTION 02 - Pictogram information was deleted.
SECTION 02 - Precautionary Statements information was deleted.
SECTION 02 - Signal Word information was deleted.
SECTION 03 - Composition information was modified.

SECTION 04 - Delayed Health Effects - Reproductive Toxicity information was modified.
 SECTION 06 - Personal Precautions, Protective Equipment and Emergency Procedures information was modified.
 SECTION 07 - Precautionary Measures information was modified.
 SECTION 08 - Engineering Control Measures information was modified.
 SECTION 08 - Occupational Exposure Limit Table information was modified.
 SECTION 08 - Personal Protective Equipment information was modified.
 SECTION 08 - Skin Protection information was modified.
 SECTION 09 - Physical/Chemical Properties information was modified.
 SECTION 11 - Reproductive Toxicity information was modified.
 SECTION 11 - Toxicological Information information was modified.
 SECTION 15 - Regulatory Information information was added.
 SECTION 15 - SARA 311 EPCRA Score information was added.
 SECTION 15 - SARA 311 EPCRA Score information was deleted.

Revision Date: August 21, 2024

ABBREVIATIONS THAT MAY HAVE BEEN USED IN THIS DOCUMENT:

TLV - Threshold Limit Value	TWA - Time Weighted Average
STEL - Short-term Exposure Limit	PEL - Permissible Exposure Limit
GHS - Globally Harmonized System	CAS - Chemical Abstract Service Number
ACGIH - American Conference of Governmental Industrial Hygienists	IMO/IMDG - International Maritime Dangerous Goods Code
API - American Petroleum Institute	SDS - Safety Data Sheet
HMIS - Hazardous Materials Information System	NFPA - National Fire Protection Association (USA)
DOT - Department of Transportation (USA)	NTP - National Toxicology Program (USA)
IARC - International Agency for Research on Cancer	OSHA - Occupational Safety and Health Administration
NCEL - New Chemical Exposure Limit	EPA - Environmental Protection Agency
SCBA - Self-Contained Breathing Apparatus	PNOS - Particles Not Otherwise Specified

Prepared according to the 29 CFR 1910.1200 (2012) by Chevron.

The information in this SDS is based on the knowledge, information, and belief of Chevron and its affiliates as of the publication date. It is not a quality specification, and no warranty, express or implied, is given. We assume no responsibility or liability for the results of using this material. The information presented here pertains only to the listed product. Since conditions of use are beyond our control, it is the user's responsibility to determine the conditions for safe use of this product and assess its suitability for their application. Users should seek additional guidance if necessary.

Diesel Exhaust Fluid (DEF)

SECTION 1. IDENTIFICATION

Product Identifier	Diesel Exhaust Fluid (DEF)
Other Means of Identification	55-124AIR, 55-124C, 55-125AIR, 55-125BTG, 55-125H2B, 55-125MER, 55-126AIR, 55-126C, 55-126MER, 55-126STPDES, 55-129AIR, 55-129AIR-1000, 55-129AIR-1250, 55-129AIR-RPV, 55-129H2B, 55-129H2B-1000, 55-129H2B-1000T, 55-129H2B-RPV, 55-129H2B-RPV-T, 55-129H2B-R-RET, 55-129H2B-RSV, 55-129H2B-RSV-T, 55-129H2B-T, 55-129OLD-1000, 55-129OPW-1250, BULK-DEF, 55-125VW, 55-125FORD, 55-125BTGEXP, 55-125CHN, 55-125GM, 55-129FLT, 55-129CHN, 55-129FLT-1000, 55-125FLT, 55-129CHN-1000, 55-129IBP, 55-129IBP-1250, 55-126IBP, 55-129RC, 55-129BLU, 55-129BLU-1000, 55-129RC-1000, 55-125RC, 55-129TRP-1000, 55-125C, 55-125TRP, 55-125, 55-125BLU, 55-125CNH, 55-126, 55-126BLU, 55-126IBP, 55-129AIR-R, 55-129CNH-1000, 55-129IBP, 55-129IBP-1250, 55-129OLD-1250, 55-129OWCB-1250, 55-125TUX, 55-129TRP, 55-125RK, 55-125h2b-tray, 55-126H2BH96, 55-126TRP, 55-126VW, 55-126BTGX80, 55-126DYNX96, 55-126CNH, 55-126FLT, 55-126FORD, 55-126RC, 55-126GM, 55-126H2B, 55-126BTG, 55-126DYN, 55-125AIRX48, 55-124H2BH52, 55-126H2BX96, 55-126CHN, BULK-DEF-40, 55-126OTR, 55-129OTR, 55-129OTR-1000, 55-126AIRH72, 55-126AIRX96, 55-126SH, 55-129FLPEXP, 55-126FLPEXP
Other Identification	Marine DEF, PTDEF-275, PTDEF-055, PTDEF-0025
Recommended Use	Please refer to Product label.
Restrictions on Use	None known.
Manufacturer/Supplier Identifier	Recochem Inc., 850 Montee de Liesse, Montreal, QC, H4T 1P4, Compliance and Regulatory Department, 905-878-5544, www.recochem.com
Other Contact Information	Yara North America Inc., The following product codes are packaged by Recochem Inc. in Canada for Yara North America Inc: 55-124AIR, 55-125AIR, 55-126AIR, 55-129AIR, 55-129AIR-1000, 55-129AIR-1250, 55-129AIR-RPV, 55-129AIR-R - 100 North Tampa St. Suite 3200, Tampa, Florida, 33602, United States, 1-877-810-4333, www.air1def.com
Emergency Phone No.	CANUTEC, 613-996-6666, 24 Hours
SDS No.	1519

SECTION 2. HAZARD IDENTIFICATION

Classification

Skin irritation - Category 3; Eye irritation - Category 2B; Specific target organ toxicity (single exposure) - Category 3

Label Elements



Signal Word:
Warning

Hazard Statement(s):

Product Identifier: Diesel Exhaust Fluid (DEF) - Ver. 1
 Date of Preparation: June 09, 2017
 Date of Last Revision: May 14, 2021

SDS No.: 1519

Page 01 of 08

H316 Causes mild skin irritation.
 H320 Causes eye irritation.
 H335 May cause respiratory irritation.

Precautionary Statement(s):

Prevention:

P261 Avoid breathing fume, mist, vapours, spray.
 P264 Wash hands thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.

Response:

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P312 Call a POISON CENTRE or doctor if you feel unwell.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P312 Call a POISON CENTRE or doctor if you feel unwell.
 P337 + P313 If eye irritation persists: Get medical advice/attention.
 P332 + P313 If skin irritation occurs: Get medical advice/attention.

Storage:

Store in a well ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable regional, national and local laws and regulations.

Other Hazards

Not applicable.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture:

Chemical Name	CAS No.	%	Other Identifiers	Other Names
Urea	57-13-6	15-40		
Free Ammonia	7664-41-7	0.1-1		

Notes

Use of Generic SDS:

If the concentration or actual concentration range of an ingredient of a particular hazardous product in the series is different from the concentration or actual concentration range disclosed for the rest of the series, either the concentration or the actual concentration range must be indicated beside that ingredient under item 3 (Composition/Information on ingredients) of the SDS. Furthermore, if any other specific information element(s) (such as flash point, numerical measure of toxicity, etc.) for a particular hazardous product in the series differs from that of the other products in the series (without affecting the classification), the information element relevant to that hazardous product must be disclosed on the SDS with an indication to which hazardous product each relates.

Source: Health Canada - Technical Guidance on the Requirements of the Hazardous Products Act and the Hazardous Products Regulations WHMIS 2015 Supplier Requirements - pg 117

SECTION 4. FIRST-AID MEASURES**First-aid Measures****Inhalation**

Remove source of exposure or move to fresh air. Call a Poison Centre or doctor if you feel unwell.

Product Identifier: Diesel Exhaust Fluid (DEF) - Ver. 1
 Date of Preparation: June 09, 2017
 Date of Last Revision: May 14, 2021

SDS No.: 1519

Page 02 of 08

Skin Contact

Avoid direct contact. Wear chemical protective clothing if necessary. Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Quickly and gently blot or brush away excess chemical. Wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 5 minutes. If skin irritation occurs, get medical advice or attention. Get medical advice or attention if you feel unwell or are concerned. Clean clothing, shoes and leather goods.

Eye Contact

Avoid direct contact. Wear chemical protective gloves if necessary. Quickly and gently blot or brush chemical off the face. Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. Remove contact lenses, if present and easy to do. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists, get medical advice or attention.

Ingestion

Rinse mouth with water. Get medical advice or attention if you feel unwell or are concerned.

First-aid Comments

Get medical advice or attention if you feel unwell or are concerned.

Most Important Symptoms and Effects, Acute and Delayed

No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Immediate Medical Attention and Special Treatment**Target Organs**

Eyes, respiratory system, skin.

Special Instructions

No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Medical Conditions Aggravated by Exposure

Dermatitis.

SECTION 5. FIRE-FIGHTING MEASURES**Extinguishing Media****Suitable Extinguishing Media**

Not combustible. Use extinguishing agent suitable for surrounding fire.

Unsuitable Extinguishing Media

None known.

Specific Hazards Arising from the Product

Does not burn. This product presents no unusual hazards in a fire situation. Closed containers may rupture violently when heated releasing contents.

In a fire, the following hazardous materials may be generated: very toxic carbon monoxide, carbon dioxide; corrosive, oxidizing nitrogen oxides.

Special Protective Equipment and Precautions for Fire-fighters

Review Section 6 (Accidental Release Measures) for important information on responding to leaks/spills.

See Skin Protection in Section 8 (Exposure Controls/Personal Protection) for advice on suitable chemical protective materials.

SECTION 6. ACCIDENTAL RELEASE MEASURES**Personal Precautions, Protective Equipment, and Emergency Procedures**

No special precautions are necessary. Use the personal protective equipment recommended in Section 8 of this safety data sheet.

Environmental Precautions

Product Identifier: Diesel Exhaust Fluid (DEF) - Ver. 1

SDS No.: 1519

Date of Preparation: June 09, 2017

Date of Last Revision: May 14, 2021

Page 03 of 08

Do not allow into any sewer, on the ground or into any waterway.

Methods and Materials for Containment and Cleaning Up

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Prevent skin contact. Do not get in eyes. Do not swallow. Avoid generating vapours or mists.

Conditions for Safe Storage

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Not available.

Appropriate Engineering Controls

The hazard potential of this product is relatively low. General ventilation is usually adequate. For large scale use of this product: use local exhaust ventilation, if general ventilation is not adequate to control amount in the air.

Individual Protection Measures

Eye/Face Protection

Not required but it is good practice to wear safety glasses or chemical safety goggles.

Skin Protection

Wear chemical protective clothing e.g. gloves, aprons, boots.
Suitable materials are: nitrile rubber.

Respiratory Protection

Not normally required if product is used as directed.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

Appearance	Clear liquid.
Odour	Ammonia-like
Odour Threshold	Not available
pH	9 - 10 (100% solution)
Melting Point/Freezing Point	-11.5 °C (11.3 °F) (melting); -11.5 °C (11.3 °F) (freezing)
Initial Boiling Point/Range	100 °C (212 °F)
Flash Point	Not applicable
Evaporation Rate	Not available
Flammability (solid, gas)	Not applicable
Upper/Lower Flammability or Explosive Limit	Not applicable (upper); Not applicable (lower)
Vapour Pressure	Not available

Product Identifier: Diesel Exhaust Fluid (DEF) - Ver. 1
Date of Preparation: June 09, 2017
Date of Last Revision: May 14, 2021

SDS No.: 1519

Page 04 of 08

Vapour Density (air = 1)	Not available
Relative Density (water = 1)	1.0000 - 1.1765 at 20 °C
Solubility	Very soluble (more than 50 g/100 mL) in water; Not available (in other liquids)
Partition Coefficient, n-Octanol/Water (Log Kow)	Not available
Auto-ignition Temperature	Not available
Decomposition Temperature	Not available
Viscosity	1.4 mm ² /s at 20 °C (kinematic); 1.4 mPa.s at 20 °C (dynamic)
Other Information	
Physical State	Liquid
Molecular Weight	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity

None known.

Chemical Stability

Normally stable.

Possibility of Hazardous Reactions

None known.

Conditions to Avoid

Contamination. High temperatures. Water, moisture or humidity. Temperatures above 135.0 °C (275.0 °F)

Incompatible Materials

Reacts explosively with: strong oxidizing agents (e.g. perchloric acid).

Not corrosive to metals.

Hazardous Decomposition Products

None known.

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure

Inhalation; skin contact; eye contact.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Urea		8471 mg/kg (rat)	> 21000 mg/kg (rabbit)
Free Ammonia	2000 ppm (rat) (4-hour exposure)	Not applicable	Not applicable

LC50: Not applicable.

LD50 (oral): Not applicable.

LD50 (dermal): Not applicable.

Skin Corrosion/Irritation

Human experience shows very mild irritation.

Serious Eye Damage/Irritation

Human experience shows very mild irritation.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

Product Identifier: Diesel Exhaust Fluid (DEF) - Ver. 1
Date of Preparation: June 09, 2017
Date of Last Revision: May 14, 2021

SDS No.: 1519

Page 05 of 08

May be harmful At high concentrations based on human experience. Nose and throat irritation.

Skin Absorption

Not harmful based on human experience.

Ingestion

Not harmful based on animal tests.

Aspiration Hazard

Not known to be an aspiration hazard.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

May cause Following skin contact: dermatitis.

May cause If inhaled: at high concentrations irritation of the respiratory system. May cause respiratory tract injury.

Respiratory and/or Skin Sensitization

No information was located. No information was located.

Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
Urea	Not Listed	Not designated	Not Listed	Not Listed
Free Ammonia	Not Listed	Not designated	Not Listed	Not Listed

Not a carcinogen.

Reproductive Toxicity

Development of Offspring

Does not cause harm to the unborn child.

Sexual Function and Fertility

Does not cause effects on sexual function or fertility.

Effects on or via Lactation

No information was located.

Germ Cell Mutagenicity

Not mutagenic.

Interactive Effects

No information was located.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Acute Aquatic Toxicity

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
Urea	Not available	Not available		
Free Ammonia	Not available	Not available		

Chronic Aquatic Toxicity

Chemical Name	NOEC Fish	EC50 Fish	NOEC Crustacea	EC50 Crustacea
Urea	Not available		Not available	
Free Ammonia	Not available		Not available	

Persistence and Degradability

No information was located.

Bioaccumulative Potential

No information was located.

Mobility in Soil

No information was located.

Other Adverse Effects

There is no information available.

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal Methods**

The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14. TRANSPORT INFORMATION

Not regulated under Canadian TDG regulations. Not regulated under US DOT Regulations.

Environmental Hazards Not applicable

Special Precautions Not applicable

Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

Proof of Dangerous Goods Classification

Date of Classification January 09, 2017

Classification Not Regulated

SECTION 15. REGULATORY INFORMATION**Safety, Health and Environmental Regulations****Canada****Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)**

All ingredients are listed on the DSL/NDSL.

USA**Toxic Substances Control Act (TSCA) Section 8(b)**

All ingredients are listed on the TSCA Inventory.

Custom Regulatory 1

Consumer Product Safety Improvement Act of 2008 General Conformity Certification

The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product container.

SECTION 16. OTHER INFORMATION

SDS Prepared By Compliance and Regulatory Department

Phone No. 905-878-5544

Date of Preparation June 09, 2017

Date of Last Revision May 14, 2021

Product Identifier: Diesel Exhaust Fluid (DEF) - Ver. 1

SDS No.: 1519

Date of Preparation: June 09, 2017

Date of Last Revision: May 14, 2021

Page 07 of 08

Revision Indicators	The following SDS content was changed on January 16, 2018: SECTION 1. IDENTIFICATION; Other Means of Identification. The following SDS content was changed on August 01, 2019: SECTION 1. IDENTIFICATION; Other Contact Information; SECTION 7. HANDLING AND STORAGE; Precautions for Safe Handling. The following SDS content was changed on January 21, 2020: SECTION 1. IDENTIFICATION; Other Means of Identification. The following SDS content was changed on January 31, 2020: SECTION 1. IDENTIFICATION; Other Means of Identification. The following SDS content was changed on November 30, 2020: SECTION 1. IDENTIFICATION; Other Means of Identification; Other Identification; SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES; Relative Density. The following SDS content was changed on March 31, 2021: SECTION 1. IDENTIFICATION; Other Means of Identification; Other Identification. The following SDS content was changed on April 26, 2021: SECTION 1. IDENTIFICATION; Other Means of Identification. The following SDS content was changed on May 14, 2021: SECTION 1. IDENTIFICATION; Other Means of Identification.
References	CHEMINFO database. Canadian Centre for Occupational Health and Safety (CCOHS).
Additional Information	We are committed to uphold the Industry Consumer Ingredient Communication Voluntary Initiative. Please send us your request by visiting our website at www.recochem.com.

Ingredients present (intentionally added ingredients) at a concentration of greater than one percent (1%) shall be listed in descending order of predominance. Ingredients present at a concentration of not more than one percent shall be listed but may be disclosed without respect to order of predominance.

Disclaimer	Notice to reader: To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.
-------------------	--

Product Identifier:	Diesel Exhaust Fluid (DEF) - Ver. 1
Date of Preparation:	June 09, 2017
Date of Last Revision:	May 14, 2021

SDS No.: 1519

Page 08 of 08

Antifreeze/Coolant

SECTION 1. IDENTIFICATION

Product Identifier	Antifreeze/Coolant
Other Means of Identification	16-242, 16-244, 16-244LAU, 16-245, 16-284, 16-284GD, 16-285, 26-248, 26-248-1000, 26-248LAU, 26-248PC, 26-249HD-1000, 26-289, 26-289-1000, 26-289PC, 26-378RLAU-1000, 26-769-1000, 26-769GR-1000, 26-929RLAU, 35-249FS, 35-759E, 36-241SO, 36-241U/N, 36-244APREXP, 36-244AX, 36-244AXEXP, 36-244C, 36-244CHR, 36-244CQ, 36-244E, 36-244FEDEXP, 36-244FS, 36-244PC, 36-244PM, 36-244PMEXP, 36-244PPEXP, 36-244PROFEXP, 36-244RAD, 36-244SH, 36-244SO, 36-244SP, 36-244SPROEXP, 36-244STP, 36-244STPEXP, 36-244TH, 36-244TOT, 36-244U/N, 36-244UFA, 36-244UG, 36-244WM, 36-244WM-S, 36-245UFA, 36-249AXEXP, 36-249CHR, 36-249E, 36-249GBW, 36-249SPROEXP, 36-249U/N, 36-254SO, 36-284CQ, 36-284E, 36-284FE, 36-284FOEXP, 36-284FS, 36-284STPEXP, 36-289E-1000, 36-289FE, 36-289FOEXP, 36-289FOEXP-1K, 36-289FS, 36-704JCBEXP, 55-929PEAK, 86-244-PRO, 86-244SY, 86-249, 86-249-1000, 86-284, 86-289, 86-699JD-1000, 86-709CAB, BULK-16240CL, BULK-16240HD, BULK-16245, BULK-16280, BULK-86245, BULK-86280, 36-249GUEXP, 36-249GUEXP-1K, 36-249LSEXP, 36-249LSEXP-1K, BULK-16720CL, 16-734GOEMF, 36-734U/N, 86-734GOEM, BULK-15720G, 16-734OOEMC, BULK-16720O, 36-734C, 36-734TOT, 86-734, 86-739-1000, BULK-15720R, 86-649JD, 16-734, 26-738-1000, 26-739, 26-739-N, 26-739PC, 26-739PC1, 36-734GD, 36-734UFA, 36-735SO, 36-735UFA, 36-739E, 36-739UFA, 86-739, 86-739SHER, BULK-16720R, 36-739SO, 26-728-1000, BULK-16720Y, BULK-86720Y, 36-774CHR, 36-779CHR, 18-108, 18-109, 18-109-1000, 18-109-40, BULK-18100, 38-109WO, 36-739LSEXP, 36-739LSEXP-1K, 36-735COA, 26-739-1000, 16-244X52
Other Identification	UF701 Coolant Concentrate, G-05 TERM ADD, Low Temperature Heat Transfer Fluid, 501 coolant concentrate
Recommended Use	Please refer to Product label.
Restrictions on Use	None known.
Manufacturer/Supplier Identifier	Recochem Inc., 850 Montee de Liesse, Montreal, QC, H4T 1P4, Compliance and Regulatory Department, 905-878-5544, www.recochem.com
Emergency Phone No.	CANUTEC, 613-996-6666, 24 Hours
SDS No.	1773

SECTION 2. HAZARD IDENTIFICATION

Classification

Acute toxicity (Oral) - Category 4; Reproductive toxicity - Category 1B; Specific target organ toxicity (repeated exposure) - Category 2

Label Elements



Signal Word:

Product Identifier: Antifreeze/Coolant - Ver. 1
Date of Preparation: September 13, 2017
Date of Last Revision: September 01, 2020

SDS No.: 1773

Page 01 of 09

Danger

Hazard Statement(s):

H302 Harmful if swallowed.

H360 May damage fertility or the unborn child.

H373 May cause damage to organs (kidneys) through prolonged or repeated exposure following skin contact and/or if swallowed.

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe fume, mist, vapours, spray.

P264 Wash hands and skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor.

P330 Rinse mouth.

P308 + P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

Storage:

Store in a well ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable regional, national and local laws and regulations.

Note:

0.1-1

. % of the mixture consists of ingredient(s) of unknown acute toxicity.

Other Hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture:

Chemical Name	CAS No.	%	Other Identifiers	Other Names
Ethylene glycol	107-21-1	80-100		
SODIUM TETRABORATE PENTAHYDRATE	12179-04-3	0.1-1		

Notes

Use of Generic SDS:

If the concentration or actual concentration range of an ingredient of a particular hazardous product in the series is different from the concentration or actual concentration range disclosed for the rest of the series, either the concentration or the actual concentration range must be indicated beside that ingredient under item 3 (Composition/Information on ingredients) of the SDS. Furthermore, if any other specific information element(s) (such as flash point, numerical measure of toxicity, etc.) for a particular hazardous product in the series differs from that of the other products in the series (without affecting the classification), the information element relevant to that hazardous product must be disclosed on the SDS with an indication to which hazardous product each relates.

Product Identifier: Antifreeze/Coolant - Ver. 1

SDS No.: 1773

Date of Preparation: September 13, 2017

Date of Last Revision: September 01, 2020

Page 02 of 09

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Remove source of exposure or move to fresh air. Call a Poison Centre or doctor if you feel unwell.

Skin Contact

Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 5 minutes. Call a Poison Centre or doctor if you feel unwell. Clean clothing, shoes and leather goods.

Eye Contact

If eye irritation persists, get medical advice or attention. Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open.

Ingestion

Rinse mouth with water. Call a Poison Centre or doctor if you feel unwell.

Most Important Symptoms and Effects, Acute and Delayed

If swallowed: There are 3 stages of effects, which can overlap. Early symptoms can include upset stomach, slurred speech, clumsiness, drowsiness, and convulsions. Second stage symptoms can include rapid heartbeat and breathing, bluish lips and skin, fluid in the lungs and heart failure. In the last stage, there can be kidney stones and kidney damage with lower back pain, and increased then decreased urine production. There may be delayed nervous system effects such as paralysis of the face, clumsiness, impaired hearing and blurred vision. Death can occur at any stage.

Immediate Medical Attention and Special Treatment

Target Organs

Digestive system, nervous system, heart, digestive system, kidneys, skin.

Special Instructions

The signs and symptoms in ethylene glycol poisoning are those of metabolic acidosis, central nervous system depression and kidney injury. Clinical chemistry may reveal anion-gap metabolic acidosis and uremia. Treatment with ethanol to inhibit the metabolism of glycol to oxalate. Early administration of ethanol may counter the toxic effects of ethylene glycol (cardiopulmonary effects attributed to metabolic acidosis and renal damage). Hemodialysis or peritoneal dialysis have been of benefit. Pre-existing respiratory and skin disorders may be aggravated by over-exposure to this product. Treat symptomatically and supportively.

Medical Conditions Aggravated by Exposure

Dermatitis.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Carbon dioxide, dry chemical powder or appropriate foam.

Unsuitable Extinguishing Media

None known.

Specific Hazards Arising from the Product

Can ignite if strongly heated.

In a fire, the following hazardous materials may be generated: irritating chemicals.

Special Protective Equipment and Precautions for Fire-fighters

Review Section 6 (Accidental Release Measures) for important information on responding to leaks/spills.

See Skin Protection in Section 8 (Exposure Controls/Personal Protection) for advice on suitable chemical protective materials.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Use the personal protective equipment recommended in Section 8 of this safety data sheet.

Environmental Precautions

Do not allow into any sewer, on the ground or into any waterway.

Methods and Materials for Containment and Cleaning Up

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Conditions for Safe Storage

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Chemical Name	ACGIH TLV®		OSHA PEL		AIHA WEEL	
	TWA	STEL	TWA	Ceiling	8-hr TWA	TWA
Ethylene glycol	10 mg/m3	100 mg/m3	Not established	50 ppm		
SODIUM TETRABORATE PENTAHYDRATE	2 mg/m3	6 mg/m3	10 mg/m3	Not established		

Appropriate Engineering Controls

The hazard potential of this product is relatively low. General ventilation is usually adequate. Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air.

Individual Protection Measures

Eye/Face Protection

Not required but it is good practice to wear safety glasses or chemical safety goggles.

Skin Protection

Wear chemical protective clothing e.g. gloves, aprons, boots.

Nitrile rubber.

Respiratory Protection

Not normally required if product is used as directed. For non-routine or emergency situations: wear a NIOSH approved air-purifying respirator with an appropriate cartridge.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

Appearance	Available in these colours: Clear, Yellow, Gold, Red, Blue, Green, Amber, Pink, Orange, Purple, White, Brown, Grey, Teal.
Odour	Not available
Odour Threshold	Not available
pH	Not available
Melting Point/Freezing Point	-13 °C (9 °F) (Ethylene glycol) (melting); -13 °C (9 °F) (Ethylene glycol) (freezing)
Initial Boiling Point/Range	197 °C (387 °F)
Flash Point	111 °C (232 °F) (closed cup) (Ethylene glycol)
Evaporation Rate	< 0.01
Flammability (solid, gas)	Not applicable
Upper/Lower Flammability or Explosive Limit	21.6 - 22.0% (Ethylene glycol) (upper); 3.2% (Ethylene glycol) (lower)
Vapour Pressure	0.090 mm Hg (0.012 kPa) at 20 °C (Ethylene glycol)
Vapour Density (air = 1)	2.14 (estimated)
Relative Density (water = 1)	1.12 - 1.15 at 20 °C (Ethylene glycol)
Solubility	Not available in water; Soluble in all proportions in ketones (e.g. acetone).
Partition Coefficient, n-Octanol/Water (Log Kow)	-1.36 at 20 °C (Ethylene glycol)
Auto-ignition Temperature	398 °C (748 °F) (Ethylene glycol)
Decomposition Temperature	Not available
Viscosity	18.86 mm ² /s at 20 °C (estimated) (kinematic); 21 mPa.s at 20 °C (estimated) (dynamic)
Other Information	
Physical State	Liquid
Molecular Weight	Not available

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions of use.

Chemical Stability

Normally stable.

Possibility of Hazardous Reactions

None known.

Conditions to Avoid

High temperatures. Open flames, sparks, static discharge, heat and other ignition sources. Temperatures above 111.0 °C (231.8 °F)

Incompatible Materials

Slightly reactive or incompatible with the following materials: oxidizing agents (e.g. peroxides), strong acids (e.g. hydrochloric acid), strong bases (e.g. sodium hydroxide).

Not corrosive to metals.

Hazardous Decomposition Products

Product Identifier: Antifreeze/Coolant - Ver. 1
Date of Preparation: September 13, 2017
Date of Last Revision: September 01, 2020

SDS No.: 1773

Page 05 of 09

Very toxic carbon monoxide, carbon dioxide.

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure

Skin contact; ingestion.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Ethylene glycol	2725 mg/m3 (rat) (4-hour exposure)	1560 mg/kg Human - Male	9530 mg/kg (rabbit)
SODIUM TETRABORATE PENTAHYDRATE	Not available	2660 mg/kg (rat)	Not available

LC50: Not applicable.

LD50 (oral): Not applicable.

LD50 (dermal): Not applicable.

Skin Corrosion/Irritation

Human experience and animal tests show mild irritation.

Serious Eye Damage/Irritation

May cause serious eye irritation based on information for closely related materials. Symptoms include sore, red eyes, and tearing.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

At high concentrations as a mist nose and throat irritation. Symptoms may include coughing, shortness of breath, difficult breathing and tightness in the chest.

Skin Absorption

At high concentrations may cause Symptoms may include redness, rash, swelling and itching.

Ingestion

Toxic, can cause death based on information for closely related materials. depression of the central nervous system, and effects on the heart and kidneys. In some cases, there may be delayed effects on the nervous system. There are 3 stages of effects, which can overlap. Early symptoms can include upset stomach, slurred speech, clumsiness, drowsiness, and convulsions. Second stage symptoms can include rapid heartbeat and breathing, bluish lips and skin, fluid in the lungs and heart failure. In the last stage, there can be kidney stones and kidney damage with lower back pain, and increased then decreased urine production. There may be delayed nervous system effects such as paralysis of the face, clumsiness, impaired hearing and blurred vision. Death can occur at any stage.

Aspiration Hazard

Not known to be an aspiration hazard.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

May cause dermatitis. Symptoms may include dry, red, cracked skin (dermatitis).

May cause Following skin contact and/or if swallowed: harmful effects on the kidneys.

Respiratory and/or Skin Sensitization

Not known to be a respiratory sensitizer. Not known to be a skin sensitizer.

Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
Ethylene glycol	Not Listed	A4	Not Listed	Not Listed
SODIUM TETRABORATE PENTAHYDRATE	Not Listed	A4	Not Listed	Not Listed

Reproductive Toxicity

Development of Offspring

If swallowed: at high concentrations animal studies show effects on the offspring. Known to cause: decreased weight. Embryotoxic (late resorptions) teratogenic(external, soft tissue and skeletal defects) may harm the unborn child.

Sexual Function and Fertility

May cause effects on sexual function and/or fertility. (Sodium Salt of Boron Acid)

Effects on or via Lactation

No information was located.

Germ Cell Mutagenicity

Not known to be a mutagen.

Interactive Effects

No information was located.

Other Information

TOXIC SUBSTANCE: KEEP AWAY FROM ANIMALS AND SMALL CHILDREN.

SECTION 12. ECOLOGICAL INFORMATION

This section is not required by WHMIS.

This section is not required by OSHA HCS 2012.

Ecotoxicity

Acute Aquatic Toxicity

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
Ethylene glycol	18500 mg/L (Oncorhynchus mykiss (rainbow trout); 96-hour; fresh water)	74000 mg/L (Daphnia magna (water flea); 24 hr)		
SODIUM TETRABORATE PENTAHYDRATE	Not available	Not available		

Chronic Aquatic Toxicity

Chemical Name	NOEC Fish	EC50 Fish	NOEC Crustacea	EC50 Crustacea
Ethylene glycol	39140 mg/L (Oncorhynchus mykiss (rainbow trout))		24000 mg/L (Daphnia magna (water flea))	
SODIUM TETRABORATE PENTAHYDRATE	Not available	Not available		

Persistence and Degradability

No information was located.

Bioaccumulative Potential

This product and its degradation products are not expected to bioaccumulate.

Mobility in Soil

No information was located.

Other Adverse Effects

There is no information available.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14. TRANSPORT INFORMATION

Not regulated under Canadian TDG regulations.

Regulation	UN No.	Proper Shipping Name	Transport Hazard Class(es)	Packing Group
US DOT	3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID (Ethylene glycol)	9	III

Environmental Hazards Not applicable (Ethylene glycol)

Special Precautions Please note: In single containers of 5000 lbs capacity or less this product is exempt from DOT regulations (non regulated). Does not require label or placards. Regulated Quantity (RQ)= 5000 lbs (2268 kg) (as ethylene glycol) For bulk shipments equal to or greater than Regulated Quantity (RQ), please adhere to classification as outlined in DOT Classification section.

Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

Proof of Dangerous Goods Classification

Date of Classification December 06, 2016
Technical Name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID
Classification 9 PG III
Classification Method As per regulation for ethylene glycol.

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

Canada

Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)

All ingredients are listed on the DSL/NDSL.

USA

Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are listed on the TSCA Inventory.

Additional USA Regulatory Lists

California Proposition 65:

WARNING: Reproductive Harm - www.P65Warnings.ca.gov/product.

Custom Regulatory 1

Consumer Product Safety Improvement Act of 2008 General Conformity Certification

The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the

Product Identifier: Antifreeze/Coolant - Ver. 1
Date of Preparation: September 13, 2017
Date of Last Revision: September 01, 2020

SDS No.: 1773

Page 08 of 09

product container.

SECTION 16. OTHER INFORMATION

SDS Prepared By	Compliance and Regulatory Department
Phone No.	905-878-5544
Date of Preparation	September 13, 2017
Date of Last Revision	September 01, 2020
Revision Indicators	The following SDS content was changed on February 02, 2018: SECTION 1. IDENTIFICATION; Other Identification. The following SDS content was changed on May 28, 2019: SECTION 1. IDENTIFICATION; Other Means of Identification. The following SDS content was changed on July 03, 2019: SECTION 1. IDENTIFICATION; Other Means of Identification. The following SDS content was changed on July 24, 2019: SECTION 1. IDENTIFICATION; Other Means of Identification; Other Identification; SECTION 2. HAZARD IDENTIFICATION; Classification; Of the following product codes: BULK-16720CL, 16-734GOEMF, 36-734U/N, 86-734GOEM, BULK-15720G, 16-734OOEMC, BULK-16720O, 36-734C, 36-734TOT, 86-734, 86-739-1000, BULK-15720R, 86-649JD, 16-734, 26-738-1000, 26-739, 26-739-N, 26-739PC, 26-739PC1, 36-734GD, 36-734UFA, 36-735SO, 36-735UFA, 36-739E, 36-739UFA, 86-739, 86-739SHER, BULK-16720R, 36-739SO, 26-728-1000, BULK-16720Y, BULK-86720Y, 36-774CHR, 36-779CHR, 18-108, 18-109, 18-109-1000, 18-109-40, BULK-18100, 38-109WO The following SDS content was changed on October 30, 2019: SECTION 1. IDENTIFICATION; Other Means of Identification. The following SDS content was changed on April 09, 2020: SECTION 1. IDENTIFICATION; Other Identification. The following SDS content was changed on September 01, 2020: SECTION 1. IDENTIFICATION; Other Means of Identification.
References	CHEMINFO database. Canadian Centre for Occupational Health and Safety (CCOHS).
Additional Information	We are committed to uphold the Industry Consumer Ingredient Communication Voluntary Initiative. Please send us your request by visiting our website at www.recochem.com. Ingredients present (intentionally added ingredients) at a concentration of greater than one percent (1%) shall be listed in descending order of predominance. Ingredients present at a concentration of not more than one percent shall be listed but may be disclosed without respect to order of predominance.
Disclaimer	Notice to reader: To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Product Identifier: Antifreeze/Coolant - Ver. 1
Date of Preparation: September 13, 2017
Date of Last Revision: September 01, 2020

SDS No.: 1773

Page 09 of 09

FICHE DE DONNÉES DE SÉCURITÉ



PROPANE

Numéro de la FDS: 000003000646

Version: 6.0

Date de révision: 2024/04/04

Date d'impression: 2024/04/22

SECTION 1. IDENTIFICATION

Nom du produit : PROPANE

Code du produit : 12021

Autres moyens d'identification : Propane HD-5, Propane commercial, gaz de pétrole liquéfié (GPL), C₃H₈, Propane de grade 1 approuvé par l'ONGC, Propane de grade 2 ap approuvé par l'ONGC, propane odorant, propane malodorant, propane pour les automobiles, ER62.

Détails concernant le fabricant ou le fournisseur

Nom du fournisseur : SUNCOR ÉNERGIE INC.
Adresse : C.P. Box 2844, 150 - 6th Avenue South-West
Calgary, Alberta T2P 3E3
Canada, Téléphone: 1-866-786-2671

Numéro d'appel d'urgence : CHEMTREC: 1-800-424-9300 (sans frais) ou +1 703-527-3887;
Suncor Energy: +1 403-296-3000

Utilisation recommandée du produit et restrictions d'utilisation

Utilisation recommandée : Le propane est utilisé comme gaz combustible, réfrigérant et gaz de laboratoire. En tant que matière première, il entre dans la composition de synthèses organiques. La qualité indique la teneur en propane. Le propane est fourni sous forme de liquide pressurisé dans des citernes.

SECTION 2. IDENTIFICATION DES DANGERS

Classement SGH en conformité avec les règlements sur les produits dangereux

Gaz inflammables : Catégorie 1

Gaz sous pression : Gaz liquéfié

Asphyxiant Simple : Catégorie 1

Éléments d'étiquetage SGH

FICHE DE DONNÉES DE SÉCURITÉ



PROPANE

Numéro de la FDS: 000003000646

Version: 6.0

Date de révision: 2024/04/04

Date d'impression: 2024/04/22

Pictogrammes de danger :



Mention d'avertissement : Danger

Mentions de danger : H220 Gaz extrêmement inflammable.
H280 Contient un gaz sous pression; peut exploser sous l'effet de la chaleur.
Peut remplacer l'oxygène et causer une suffocation rapide.

Conseils de prudence : **Prévention:**
P210 Tenir à l'écart de la chaleur, des surfaces chaudes, des étincelles, des flammes nues et de toute autre source d'inflammation. Ne pas fumer.
Intervention:
P377 Fuite de gaz enflammé: Ne pas éteindre si la fuite ne peut pas être arrêtée sans danger.
P381 En cas de fuite, éliminer toutes les sources d'ignition.
Stockage:
P410 + P403 Protéger du rayonnement solaire. Stocker dans un endroit bien ventilé.

Autres dangers

Aucun(e) à notre connaissance.

SECTION 3. COMPOSITION/ INFORMATIONS SUR LES COMPOSANTS

Substance/mélange : Mélange

Composants

Nom Chimique	Nom commun/Synonyme	No.-CAS	Concentration (%)
propane	propane	74-98-6	72 - 100
propène	propène	115-07-1	<= 23.8
butane	butane	106-97-8	<= 4.7
éthane	éthane	74-84-0	<= 4.6
isobutane	isobutane	75-28-5	<= 3.6
isopentane	isopentane	78-78-4	<= 1
pentane	pentane	109-66-0	<= 0.9
but-1-ène	but-1-ène	106-98-9	<= 0.5
méthane	méthane	74-82-8	<= 0.2

Toutes les concentrations ci-dessus sont en pourcentage par volume.

SECTION 4. PREMIERS SECOURS

FICHE DE DONNÉES DE SÉCURITÉ



PROPANE

Numéro de la FDS: 000003000646

Version: 6.0

Date de révision: 2024/04/04

Date d'impression: 2024/04/22

En cas d'inhalation	: Amener la victime à l'air libre. Respiration artificielle et/ou oxygène peuvent être nécessaires. Demander conseil à un médecin.
En cas de contact avec la peau	: En cas de contact, rincer immédiatement avec beaucoup d'eau pendant au moins 15 minutes en retirant les vêtements et chaussures contaminés. Laver la peau à fond avec de l'eau et du savon ou utiliser un produit reconnu pour le nettoyage de la peau. Laver les vêtements contaminés avant de les réutiliser. Demander conseil à un médecin.
En cas de contact avec les yeux	: Enlever les lentilles de contact. Rincer immédiatement et abondamment à l'eau, y compris sous les paupières, pendant au moins 15 minutes. Appeler un médecin.
En cas d'ingestion	: Ne présente pas une voie d'exposition significative.
Principaux symptômes et effets, aigus et différés	: L'inhalation peut affecter le système nerveux central. L'inhalation des vapeurs peut causer de la somnolence, des maux de tête, des étourdissements et de la confusion. Peut irriter le système respiratoire. Un contact avec le gaz en expansion rapide peut provoquer des brûlures ou des gelures. La surexposition peut entraîner une sensibilisation cardiaque. Des concentrations élevées peuvent déplacer l'oxygène et provoquer des vertiges ou la suffocation.
Indication des éventuels soins médicaux immédiats et traitements particuliers nécessaires	: Traitement symptomatique requis. Contactez le spécialiste en traitement de poison immédiatement si de grandes quantités ont été ingérées ou inhalées.

SECTION 5. MESURES DE LUTTE CONTRE L'INCENDIE

Moyens d'extinction appropriés	: Utiliser des moyens d'extinction appropriés aux conditions locales et à l'environnement proche.
Moyens d'extinction inappropriés	: Pas d'information disponible.
Dangers spécifiques pendant la lutte contre l'incendie	: Si la fuite de produit ne peut pas être coupée sans risque, laisser le produit se consumer. Refroidir par pulvérisation d'eau les récipients fermés se trouvant à proximité de la source d'incendie.
Produits de combustion dangereux	: Oxydes de carbone (CO, CO ₂), fumée et vapeurs irritantes comme produits d'une combustion incomplète.

FICHE DE DONNÉES DE SÉCURITÉ



PROPANE

Numéro de la FDS: 000003000646

Version: 6.0

Date de révision: 2024/04/04

Date d'impression: 2024/04/22

- Information supplémentaire : Empêcher les eaux d'extinction du feu de contaminer les eaux de surface ou le réseau d'alimentation souterrain.
- Équipements de protection particuliers des pompiers : Porter un appareil respiratoire autonome et un équipement de protection complet.
Utiliser un respirateur à air comprimé équipé d'un masque intégral.

SECTION 6. MESURES À PRENDRE EN CAS DE DISPERSION ACCIDENTELLE

- Précautions individuelles, équipement de protection et procédures d'urgence : Pour l'équipement de protection individuel, voir rubrique 8.
Assurer une ventilation adéquate.
Évacuer le personnel vers des endroits sûrs.
Lorsque la ventilation du local est insuffisante porter un équipement de protection respiratoire.
Enlever toute source d'ignition.
Faire attention à l'étalement du gaz au sol (plus lourd que l'air) et à la direction du vent.
Marquer la zone contaminée avec des panneaux et en interdire l'accès à toute personne non autorisée.
Seul le personnel qualifié équipé d'un équipement individuel de protection adapté peut intervenir.
- Précautions pour la protection de l'environnement : En cas de pollution de cours d'eau, lacs ou égouts, informer les autorités compétentes conformément aux dispositions locales.
- Méthodes et matériel de confinement et de nettoyage : Éviter tout déversement ou fuite supplémentaire, si cela est possible en toute sécurité.
Assurer une ventilation adéquate.
Utiliser un équipement de ventilation antidéflagrant.
Utiliser des outils ne provoquant pas d'étincelles.
Contacter les autorités locales compétentes.

SECTION 7. MANIPULATION ET STOCKAGE

- Conseils pour une manipulation sans danger : Pour l'équipement de protection individuel, voir rubrique 8.
Ne pas manger, fumer ou boire dans la zone de travail.
En cas de ventilation insuffisante, porter un appareil respiratoire approprié.
Éviter le contact avec la peau, les yeux et les vêtements.
Éviter de respirer les gaz.
Éviter les sources d'ignition. Fixer et mettre à la terre les réservoirs et l'équipement. Ces mesures peuvent toutefois être insuffisantes pour décharger l'électricité statique.
N'utiliser qu'avec une ventilation adéquate.
Tenir à l'écart de la chaleur et des sources d'ignition.
Conserver le conteneur fermé lorsqu'il n'est pas utilisé.
Ne pas utiliser des outils qui peuvent provoquer des étincelles.

FICHE DE DONNÉES DE SÉCURITÉ



PROPANE

Numéro de la FDS: 000003000646

Version: 6.0

Date de révision: 2024/04/04

Date d'impression: 2024/04/22

Ne pas pénétrer dans les zones où l'on utilise ou stocke [cette matière] sans une ventilation adéquate.

Conditions de stockage : Conserver dans le conteneur d'origine.
sures : Refermer soigneusement tout récipient entamé et le stocker verticalement afin d'éviter tout écoulement.
Conserver dans un endroit sec, frais et bien ventilé.
Conserver dans des conteneurs proprement étiquetés.
Pour conserver la qualité du produit, ne pas stocker à la chaleur ni au soleil.
Conserver à l'écart de toute flamme ou source d'étincelles - Ne pas fumer.
Assurer que les contenants entreposés sont mis à la terre ou mis à la masse.

SECTION 8. CONTRÔLES DE L'EXPOSITION/ PROTECTION INDIVIDUELLE

Composants avec valeurs limites d'exposition professionnelle

Composants	No.-CAS	Type de valeur (Type d'exposition)	Paramètres de contrôle / Concentration admissible	Base
propane	74-98-6	TWA	1,000 ppm	CA AB OEL
		VEMP	1,000 ppm 1,800 mg/m3	CA QC OEL
propène	115-07-1	TWA	500 ppm	CA BC OEL
		VEMP	500 ppm	CA QC OEL
		TWA	500 ppm	ACGIH
butane	106-97-8	TWA	1,000 ppm	CA AB OEL
		TWA	1,000 ppm	CA BC OEL
		VEMP	800 ppm 1,900 mg/m3	CA QC OEL
		STEL	1,000 ppm	ACGIH
éthane	74-84-0	TWA	1,000 ppm	CA AB OEL
isobutane	75-28-5	TWA	1,000 ppm	CA AB OEL
		TWA	1,000 ppm	CA BC OEL
		STEL	1,000 ppm	ACGIH
isopentane	78-78-4	VEMP	1,000 ppm	CA QC OEL
		TWA	1,000 ppm	CA BC OEL
		TWA	600 ppm	CA AB OEL
		TWA	1,000 ppm	ACGIH

Mesures d'ordre technique : Assurer une ventilation adéquate pour faire en sorte que la limite d'exposition en milieu de travail ne soit pas dépassée.
Utiliser seulement dans des zones bien ventilées.
Utiliser un équipement de ventilation antidéflagrant.

Équipement de protection individuelle

Protection respiratoire : Le choix du respirateur doit être fondé en fonction des ni-

FICHE DE DONNÉES DE SÉCURITÉ



PROPANE

Numéro de la FDS: 000003000646

Version: 6.0

Date de révision: 2024/04/04

Date d'impression: 2024/04/22

veaux d'expositions prévus ou connus, du danger que représente le produit et des limites d'utilisation sécuritaire du respirateur retenu.

Filtre de type : Toujours porter un appareil de protection respiratoire autonome approuvé par le NIOSH pour la manipulation de cette substance.

Protection des mains
Matériel : Porter des gants doublés afin de prévenir les engelures. Informez-vous auprès de votre fournisseur d'équipement de protection individuelle pour connaître le temps de protection offert et le type de gants le mieux adapté à vos besoins. Il est à noter que peu importe leur degré d'imperméabilité, tout type de matériel va éventuellement devenir perméable aux produits chimiques. Il est donc important de vérifier régulièrement l'état de ses gants de protection. Aux premiers signes de durcissement ou de fissure du matériel, ils devraient être changés.

Remarques : Lors de la manipulation de produits chimiques, porter en permanence des gants étanches et résistants aux produits chimiques conformes à une norme approuvée, si une évaluation du risque indique que cela est nécessaire.

Protection des yeux : Portez des lunettes de sécurité avec écrans latéraux ou des lunettes.

Protection de la peau et du corps : Choisir une protection corporelle en relation avec le type, la concentration et les quantités de substances dangereuses, et les spécificités du poste de travail.

Mesures de protection : Laver les vêtements contaminés avant de les remettre. Porter un équipement de protection adéquat.

Mesures d'hygiène : Enlever et laver les gants, y compris l'intérieur, et les vêtements contaminés avant la réutilisation. Se laver le visage, les mains et toute partie de la peau exposée soigneusement après manipulation.

SECTION 9. PROPRIÉTÉS PHYSIQUES ET CHIMIQUES

Aspect : Gaz à température ambiante; liquide lorsque entreposé sous pression, gaz comprimé liquéfié

Couleur : incolore

Odeur : Propane est un gaz inodore. Le propane odorant peut contenir

FICHE DE DONNÉES DE SÉCURITÉ



PROPANE

Numéro de la FDS: 000003000646

Version: 6.0

Date de révision: 2024/04/04

Date d'impression: 2024/04/22

jusqu'à 30 g d'éthyl mercaptan par 1000 L de propane.

Seuil olfactif : Donnée non disponible

pH : Donnée non disponible

Point de fusion/point de congélation : Donnée non disponible

Point initial d'ébullition et intervalle d'ébullition : -42 °C

Point d'éclair : -104 °C

Méthode: coupelle fermée

Taux d'évaporation : Donnée non disponible

Inflammabilité (solide, gaz) : Gaz extrêmement inflammable.

Limite d'explosivité, supérieure / Limite d'inflammabilité supérieure : 9.5 % (v)

Limite d'explosivité, inférieure / Limite d'inflammabilité inférieure : 2.1 % (v)

Pression de vapeur : 10,763 mmHg (38 °C)

Densité de vapeur relative : 1.56

Densité relative : Donnée non disponible

Densité : Donnée non disponible

Solubilité(s)

Hydrosolubilité : Donnée non disponible

Coefficient de partage: n-octanol/eau : Donnée non disponible

Température d'auto-inflammation : 450 °C

Température de décomposition : Donnée non disponible

Viscosité

Viscosité, cinématique : Donnée non disponible

PROPANE

Numéro de la FDS: 000003000646

Version: 6.0

Date de révision: 2024/04/04

Date d'impression: 2024/04/22

SECTION 10. STABILITÉ ET RÉACTIVITÉ

Réactivité	:	Pas de réactions dangereuses connues dans les conditions normales d'utilisation.
Stabilité chimique	:	Stable dans des conditions normales.
Possibilité de réactions dangereuses	:	Une polymérisation dangereuse ne se produit pas.
Conditions à éviter	:	Chaleur, flammes et étincelles.
Matières incompatibles	:	Réactif avec agents oxydants et composés halogénés.
Produits de décomposition dangereux	:	Susceptible de dégager des COx, fumées et vapeurs irritantes, en présence de chaleur jusqu'à décomposition.

SECTION 11. INFORMATIONS TOXICOLOGIQUES

Informations sur les voies d'exposition probables

Contact avec les yeux

Inhalation

Contact avec la peau

Toxicité aiguë

Produit:

Toxicité aiguë par voie orale	:	Remarques: Compte tenu des données disponibles, les critères de classification ne sont pas remplis.
Toxicité aiguë par inhalation	:	Remarques: Compte tenu des données disponibles, les critères de classification ne sont pas remplis.
Toxicité aiguë par voie cutanée	:	Remarques: Compte tenu des données disponibles, les critères de classification ne sont pas remplis.

Composants:**butane:**

Toxicité aiguë par inhalation	:	CL50 (Rat): 658 mg/L Durée d'exposition: 4 H Atmosphère de test: gaz
-------------------------------	---	--

isopentane:

Toxicité aiguë par inhalation	:	CL50 (Rat): 280 mg/L Durée d'exposition: 4 H Atmosphère de test: vapeur
-------------------------------	---	---

FICHE DE DONNÉES DE SÉCURITÉ



PROPANE

Numéro de la FDS: 000003000646

Version: 6.0

Date de révision: 2024/04/04

Date d'impression: 2024/04/22

pentane:

Toxicité aiguë par voie orale : DL50 (Rat): > 2,000 mg/kg

Toxicité aiguë par inhalation : CL50 (Rat): 364 mg/L
Durée d'exposition: 4 H
Atmosphère de test: vapeur

Corrosion cutanée/irritation cutanée

Compte tenu des données disponibles, les critères de classification ne sont pas remplis.

Lésions oculaires graves/irritation oculaire

Compte tenu des données disponibles, les critères de classification ne sont pas remplis.

Sensibilisation respiratoire ou cutanée

Sensibilisation cutanée

Compte tenu des données disponibles, les critères de classification ne sont pas remplis.

Sensibilisation respiratoire

Compte tenu des données disponibles, les critères de classification ne sont pas remplis.

Mutagenicité sur les cellules germinales

Compte tenu des données disponibles, les critères de classification ne sont pas remplis.

Cancérogénicité

Compte tenu des données disponibles, les critères de classification ne sont pas remplis.

Toxicité pour la reproduction

Compte tenu des données disponibles, les critères de classification ne sont pas remplis.

Toxicité spécifique pour certains organes cibles - exposition unique

Compte tenu des données disponibles, les critères de classification ne sont pas remplis.

Toxicité spécifique pour certains organes cibles - exposition répétée

Compte tenu des données disponibles, les critères de classification ne sont pas remplis.

SECTION 12. INFORMATIONS ÉCOLOGIQUES

Écotoxicité

Produit:

Toxicité pour les poissons : Remarques: Donnée non disponible

Toxicité pour la daphnie et les autres invertébrés aquatiques : Remarques: Donnée non disponible

Toxicité pour les algues/plantes aquatiques : Remarques: Donnée non disponible

Toxicité pour les microorganismes : Remarques: Donnée non disponible

FICHE DE DONNÉES DE SÉCURITÉ



PROPANE

Numéro de la FDS: 000003000646

Version: 6.0

Date de révision: 2024/04/04

Date d'impression: 2024/04/22

Persistance et dégradabilité

Produit:

Biodégradabilité : Remarques: Donnée non disponible

Potentiel de bioaccumulation

Donnée non disponible

Mobilité dans le sol

Donnée non disponible

Autres effets néfastes

Donnée non disponible

SECTION 13. CONSIDÉRATIONS RELATIVES À L'ÉLIMINATION

Méthodes d'élimination

Déchets de résidus : Empêcher le produit de pénétrer dans les égouts, les cours d'eau ou le sol.
Remettre les excédents et les solutions non recyclables à une entreprise d'élimination des déchets agréée.
Les déchets doivent être classés et étiquetés avant leur recyclage ou leur élimination.
Envoyer à une entreprise autorisée à gérer les déchets.
Éliminer les déchets dangereux en conformité avec les réglementations locales et nationales.
Éliminer les résidus du produit conformément aux instructions de la personne responsable de l'élimination des déchets.

Emballages contaminés : Communiquer avec les autorités locales ou l'unité commerciale pour connaître les instructions d'élimination du produit.

SECTION 14. INFORMATIONS RELATIVES AU TRANSPORT

Réglementations internationales

IATA-DGR

UN/ID No. : UN 1978
Nom d'expédition des Nations unies : Propane
Classe : 2.1
Groupe d'emballage : Non réglementé
Étiquettes : Flammable Gas
Instructions de conditionnement (avion cargo) : 200

Code IMDG

Numéro ONU : UN 1978
Nom d'expédition des Nations unies : PROPANE

FICHE DE DONNÉES DE SÉCURITÉ



PROPANE

Numéro de la FDS: 000003000646

Version: 6.0

Date de révision: 2024/04/04

Date d'impression: 2024/04/22

tions unies
Classe : 2.1
Groupe d'emballage : Non réglementé
Étiquettes : 2.1
EmS Code : F-D, S-U
Polluant marin : non

Transport en vrac conformément à l'annexe II de la convention Marpol 73/78 et au recueil IBC

Non applicable pour le produit tel qu'il est fourni.

Réglementation nationale

TDG

Numéro ONU : UN 1978
Nom d'expédition des Nations unies : PROPANE
Classe : 2.1
Groupe d'emballage : Non réglementé
Étiquettes : 2.1
Code ERG : 115
Polluant marin : non
Remarques : ERAP 2-0010-058

Précautions particulières à prendre par l'utilisateur

La(Le)s classification(s) de transport fournie(s) ici servent uniquement à des fins d'information et est(sont) basé(e)s sur les propriétés des matières non emballées, tel que décrit dans la fiche des caractéristiques de sécurité. Les classifications de transport peuvent varier selon le mode de transport, les tailles des emballages et les variations dans les réglementations régionales ou nationales.

SECTION 15. INFORMATIONS RELATIVES À LA RÉGLEMENTATION

NPRI Composants : propane
propène
butane
isobutane
isopentane
pentane
but-1-ène
n-hexane

Les composants de ce produit figurent dans les inventaires suivants:

TCSI : Listé ou en conformité avec l'inventaire
TSCA : Toutes les substances sont notifiées actives sur l'inventaire de la loi sur le contrôle des substances toxiques (TSCA)
DSL : Tous les composants de ce produit sont sur la liste canadienne LIS
ENCS : Listé ou en conformité avec l'inventaire

FICHE DE DONNÉES DE SÉCURITÉ



PROPANE

Numéro de la FDS: 000003000646

Version: 6.0

Date de révision: 2024/04/04

Date d'impression: 2024/04/22

ISHL	: Listé ou en conformité avec l'inventaire
KECI	: Listé ou en conformité avec l'inventaire
PICCS	: Listé ou en conformité avec l'inventaire
IECSC	: Listé ou en conformité avec l'inventaire

Listes canadiennes

Aucune substance n'est soumise à une déclaration de nouvelle activité significative.

SECTION 16. AUTRES INFORMATIONS

Texte complet pour autres abréviations

ACGIH	: USA. ACGIH ACGIH, valeurs limites d'exposition (TLV)
CA AB OEL	: Canada. Alberta, Code de santé et de sécurité au travail (tableau 2 : VLE)
CA BC OEL	: Canada. LEP Colombie Britannique
CA QC OEL	: Québec. Règlement sur la santé et la sécurité du travail, Annexe 1 Partie 1: Valeurs d'exposition admissibles des contaminants de l'air
ACGIH / TWA	: 8 heures, moyenne pondérée dans le temps
ACGIH / STEL	: Limite d'exposition à court terme
CA AB OEL / TWA	: Moyenne pondérée dans le temps de 8 h
CA AB OEL / TWA	: Limite d'exposition professionnelle de 8 heures
CA BC OEL / TWA	: Moyenne pondérée dans le temps de 8 h
CA QC OEL / VEMP	: Valeur d'exposition moyenne pondérée

AIIC - Inventaire australien des produits chimiques industriels; ANTT - Agence nationale pour le transport par terre du Brésil; ASTM - Société américaine pour les essais de matériaux; bw - Poids corporel; CMR - Cancérogène, mutagène ou toxique pour la reproduction; DIN - Norme de l'Institut allemand de normalisation; DSL - Liste nationale des substances (Canada); ECx - Concentration associée à x % de réponse; ELx - Taux de charge associée à x % de réponse; EmS - Horaire d'urgence; ENCS - Substances chimiques existantes et substances nouvelles (Japon); ErCx - Concentration associée à une réponse de taux de croissance de x %; ERG - Guide d'intervention d'urgence; GHS - Système général harmonisé; GLP - Bonnes pratiques de laboratoire; IARC - Centre international de recherche sur le cancer; IATA - Association du transport aérien international; IBC - Code international pour la construction et l'équipement des navires transportant des produits chimiques dangereux en vrac; IC50 - Concentration inhibitrice demi maximale; ICAO - Organisation de l'aviation civile internationale; IECSC - Inventaire des substances chimiques existantes en Chine; IMDG - Marchandises dangereuses pour le transport maritime international; IMO - Organisation maritime internationale; ISHL - Sécurité industrielle et le droit de la santé (Japon); ISO - Organisation internationale de normalisation; KECI - Inventaire des produits chimiques coréens existants; LC50 - Concentration létale pour 50 % d'une population test; LD50 - Dose létale pour 50 % d'une population test (dose létale moyenne); MARPOL - Convention internationale pour la prévention de la pollution par les navires; n.o.s. - Non spécifié; Nch - Norme chilienne; NO(A)EC - Effet de concentration non observé (négatif); NO(A)EL - Effet non observé

FICHE DE DONNÉES DE SÉCURITÉ



PROPANE

Numéro de la FDS: 000003000646

Version: 6.0

Date de révision: 2024/04/04

Date d'impression: 2024/04/22

(nocif); NOELR - Taux de charge sans effet observé; NOM - Norme Officielle mexicaine; NTP - Programme de toxicologie national; NZIoC - Inventaire des produits chimiques en Nouvelle-Zélande; OECD - Organisation pour la coopération économique et le développement; OPPTS - Bureau de la sécurité chimique et prévention de la pollution; PBT - Persistant, bio-accumulable et toxique; PICCS - Inventaire des produits et substances chimiques aux Philippines; (Q)SAR - Relations structure-activité (quantitative); REACH - Règlement (CE) n° 1907/2006 du Parlement européen et du Conseil concernant l'enregistrement, l'évaluation, l'autorisation et la restriction des produits chimiques; SADT - Température de décomposition auto-accélérée; SDS - Fiche de Données de Sécurité; TCSI - Inventaire des substances chimiques à Taiwan; TDG - Transport des marchandises dangereuses; TECl - Répertoire des produits chimiques existants en Thaïlande; TSCA - Loi sur le contrôle des substances toxiques (États-Unis); UN - Les Nations Unies; UNRTDG - Recommandations des Nations Unies relatives au transport des marchandises dangereuses; vPvB - Très persistant et très bioaccumulable; WHMIS - Système d'information sur les matières dangereuses utilisées au travail

Date de révision : 2024/04/04

Les informations contenues dans la présente fiche de sécurité ont été établies sur la base de nos connaissances à la date de publication de ce document. Ces informations ne sont données qu'à titre indicatif en vue de permettre des opérations de manipulation, fabrication, stockage, transport, distribution, mise à disposition, utilisation et élimination dans des conditions satisfaisantes de sécurité, et ne sauraient donc être interprétées comme une garantie ou considérées comme des spécifications de qualité. Ces informations ne concernent en outre que le produit nommé désigné et, sauf indication contraire spécifique, peuvent ne pas être applicables en cas de mélange dudit produit avec d'autres substances ou utilisables pour tout procédé de fabrication.

CA / FR